

# Package ‘IRISseismic’

October 16, 2022

**Type** Package

**Version** 1.6.6

**Title** Classes and Methods for Seismic Data Analysis

**Depends** R (>= 3.1.0)

**Imports** methods, pracma, RCurl, seismicRoll (>= 1.1.0), signal,  
stringr, XML, stats

**Suggests** knitr,rmarkdown

**VignetteBuilder** knitr

**Description** Provides classes and methods for seismic data analysis. The base classes and methods are inspired by the python code found in the 'ObsPy' python toolbox <<https://github.com/obspy/obspy>>. Additional classes and methods support data returned by web services provided by the 'IRIS DMC' <<http://service.iris.edu/>>.

**Collate** Class-Trace.R Class-Stream.R Class-IrisClient.R  
mseedWrappers.R Utils.R spectralUtils.R

**License** GPL (>= 2)

**Repository** CRAN

**NeedsCompilation** yes

**Author** Jonathan Callahan [aut],  
Rob Casey [aut],  
Gillian Sharer [aut, cre],  
Mary Templeton [aut],  
Chad Trabant [ctb]

**Maintainer** Gillian Sharer <[gillian@iris.washington.edu](mailto:gillian@iris.washington.edu)>

**Date/Publication** 2022-10-16 00:26:27 UTC

## R topics documented:

IRISseismic-package . . . . .	3
basicStats . . . . .	11
butterworth . . . . .	12

crossSpectrum . . . . .	14
DDT . . . . .	17
envelope . . . . .	18
eventWindow . . . . .	19
getAvailability . . . . .	21
getChannel . . . . .	23
getDataAvailability . . . . .	25
getDataselect . . . . .	28
getDistaz . . . . .	30
getEvalresp . . . . .	31
getEvent . . . . .	32
getGaps . . . . .	34
getNetwork . . . . .	35
getRotation . . . . .	37
getSNCL . . . . .	39
getStation . . . . .	40
getTimeSeries . . . . .	42
getTraveltime . . . . .	44
getUnavailability . . . . .	46
getUpDownTimes . . . . .	48
hilbert . . . . .	50
hilbertFFT . . . . .	51
IrisClient-class . . . . .	52
McNamaraBins . . . . .	54
McNamaraPSD . . . . .	55
mergeTraces . . . . .	56
mergeUpDownTimes . . . . .	57
miniseed2Stream . . . . .	59
multiplyBy . . . . .	60
noiseMatrix2PdfMatrix . . . . .	61
noiseModels . . . . .	63
psdDF2NoiseMatrix . . . . .	64
psdList . . . . .	65
psdList2NoiseMatrix . . . . .	67
psdPlot . . . . .	68
psdStatistics . . . . .	70
readMiniseedFile . . . . .	71
rms . . . . .	73
rotate2D . . . . .	74
slice . . . . .	76
STALTA . . . . .	77
Stream-class . . . . .	80
surfaceDistance . . . . .	83
Trace-class . . . . .	84
TraceHeader-class . . . . .	86
transferFunctionSpectra . . . . .	87
triggerOnset . . . . .	88
unHistogram . . . . .	90

---

IRISseismic-package    *Classes and methods for seismic data analysis*

---

## Description

This package provides S4 classes for downloading and processing seismological data available from the IRIS Data Management Center (DMC) (<http://ds.iris.edu/ds/nodes/dmc/>). Core classes Trace, Stream and IrisClient and their associated methods are inspired by the functionality available in the python ObsPy package (<http://obspy.org/>).

## Introduction

The "IRISseismic-intro" vignette gives introductory examples on using the package.

## History

version 1.6.6

- for web service calls that support the nodata=<204|404> option, use nodata=204
- corrected the crossSpectrum documentation, Pxy is the cross-periodogram for ts1 and ts2

version 1.6.5

- examples and vignette updated for better error handling when accessing internet resources

version 1.6.4

- updated to (modified version of) libmseed-2.19.8

version 1.6.3

- Stream object @ timing\_quality now averages the values of the miniSEED blockette 1001 timing quality values, instead of summing the blockette 1001 values and dividing by the number of records

version 1.6.2

- getDataselect, modified default time out values
- fixed url in documentation

version 1.6.0

- irisNetrc definition moved inside getDataselect function
- restored getTimeSeries function
- default values for class Trace InstrumentSensitivity and SensitivityFrequency changed to NA from 1.0
- added transferFunctionSpectra function

version 1.5.2

- updated `getDataAvailability` to use new `fdsnws` availability web service specification <http://service.iris.edu/fdsnws/availability/>
- fixed bug in `getDataAvailability` when `mergequality=FALSE`
- fixed bug in `getDataAvailability` affecting start/end times, introduced in version 1.5.1
- fixed bug in `mergeTraces` when trace has gap at end, introduced in version 1.5.1

#### version 1.5.1

- changed a subset of time format OS to OS6
- fixed bug in `mergeTraces` when `fdsnws/dataselect` implementation cuts on records instead of sample

#### version 1.5.0

- added `spacing` as an option to `getEvalresp`
- modified `getEvalresp` to use `IrisClient` `service_type`
- new `getDataAvailability()` to return dataframe of miniseed data extents in the IRIS archive using IRIS web service <http://service.iris.edu/irisws/availability/1/>
- minor change to `src` code to pass CRAN checks

#### version 1.4.9

- additional error handling
- minor updates to the `plot.Trace` and `plot.Stream` functions
- updated `src/libmseed` to version 2.19.6

#### version 1.4.8

- updated `src/libmseed` to version 2.19.5
- fix bug related to leap seconds
- functions that call web services now follow redirects
- some error outputs have changed slightly
- `rmsVariance` function, `na.rm=TRUE` calculates data length minus NA values
- `rmsVariance.Stream` now honors `na.rm=TRUE`
- `getGaps()` error handling now checks for negative sample rates
- `getEvent`, `getEvalresp` now truncates start and end input times to seconds (time format OS0 instead of OS) to fix error when user set `options(digits.secs=) > 3`

#### version 1.4.7

- additional error handling for `getDistaz`
- added input `service_type` to `IrisClient`, defaults to `fdsnws`
- `plot.Trace` x-axis labels are "MM dd" instead of days of week for traces > 1 day and < 1 week
- `getDataselect` will retry once if it encounters http code 401
- additional error handling for `spectralUtils`

#### version 1.4.6

- bug fix for IRISSeismic::slice

version 1.4.5

- fixed bug in noiseModels for low noise model results at periods > 10000 seconds
- retry if getEvent returns a service unavailable message

version 1.4.4

- modified error messages for getEvalresp() and getDistaz()

version 1.4.3

- changed getEvent default url from <http://earthquake.usgs.gov/fdsnws/event/1/> to <https://earthquake.usgs.gov/fdsnws/event/1/>

version 1.4.2

- updated libmseed version to 2.19

version 1.4.1

- updated libmseed version to 2.18
- fix for reading miniseed with out of order records

version 1.4.0

- addition of repository argument to getDataselect and getSNCL, to match change in fdsnws-dataselect web service

version 1.3.9

- fixes compile warning generated by clang
- removes followlocation=TRUE from getDataselect RCurl options

version 1.3.8

- getDataselect does not add a quality indicator to url by default. IRIS webservices itself defaults to quality="M"
- getStation and getChannel do not add includerestricted indicator to url by default. IRIS webservices itself defaults to TRUE
- better handling of textConnections

version 1.3.7

- users can now supply instrument response information in the form of frequency, amplitude, phase to the functions psdStatistics, psdList2NoiseMatrix, psdPlot, in place of the getEvalresp webservice call. Function argument order for psdPlot is changed.
- added showMedian option to psdPlot

version 1.3.5

- added ignoreEpoch option to getDataselect

version 1.3.4 – webservices and plotting

- `getEvent` forwards `http://service.iris.edu/fdsnws/event/1/` calls to `http://earthquake.usgs.gov/fdsnws/event/1/`
- `getDistaz` changes output dataframe column name `ellipsoid.attrs` to `ellipsoid.name`
- `plot.Trace` allows for user supplied `ylab` and `xlab` input

#### version 1.3.3 – documentation

- Updated documentation and corrected outdated links

#### version 1.3.2 – bug fix

- `noiseModels()`, minor correction to the New High Noise Model

#### version 1.3.1 – bug fixes

- `psdStatistics()` correctly handles NA values when calculating high and low PDF bin limits and returns `pct_above` and `pct_below` vectors of correct length

#### version 1.3.0 – compatibility with IRIS webservice

- `getDistaz()` returns new variables from output of `http://services.iris.edu/irisws/distaz/1/`

#### version 1.2.2 – PDF bug fix

- `psdList2NoiseMatrix()` adds 1 second to start time in `getEvalresp` call to work around a quirk in `http://services.iris.edu/irisws/evalresp/1/` webservice that will not return a response if the start time is exactly on a metadata epoch boundary.

#### version 1.2.1 – PDF

- `psdPlot()` now compatible with changes to `psdStatistics()` in previous version. Adds `ylo`, `yhi` arguments to customize y-axis limits in plot.

#### version 1.2.0 – PDF

- `psdStatistics()` changes method of setting PDF bins from fixed values to bins based on the high and low PSD values and shifts bin centers by 0.5 dB. The result now matches output from `http://services.iris.edu/mustang/noise-pdf`.

#### version 1.1.7 – improved error handling

- `getDataselect()`, `getNetwork()`, `getStation()`, `getChannel()`, `getAvailability()`, `getEvalresp()`, `getTraveltime()` error handling now report unexpected http status codes.

#### version 1.1.6 – bug fixes

- `getGaps()` fixes issues with multiple sample rates and setting minimum gap length.
- `mergeTraces.Stream()` relaxes criteria for acceptable sample rate jitter.

#### version 1.1.5 – trace rotation

- `rotate2D()` changes orthogonality test tolerance from 5 degrees to 3 degrees.

#### version 1.1.4 – trace rotation

- `rotate2D()` exits if traces are not orthogonal.

version 1.1.3 – bug fix

- psdStatistics() fixes bug in calculation of pct\_above and pct\_below.

version 1.1.1 – bug fixes

- getGaps() minor bug fix.
- mergeTraces.Stream() minor bug fix.

version 1.0.10 – new data request argument and bug fixes

- Imports seismicRoll ( $\geq 1.1.0$ ).
- getGaps() fixes bugs in calculation of initial and final gap of Trace.
- getDataselect(), getSNCL() adds "inclusiveEnd" argument, a logical that determines whether a data point that falls exactly on the requested endtime is included in the Trace.
- libmseed change, when multiple sample rates exist in miniseed records use the mode of all sample rates instead of using the sample rate in the first record.
- psdList() added rule for octave generation for channel codes that start with "V".

version 1.0.9 – Trace class expansion and bug fixes

- Improved error handling for getAvailability(), getChannel(), getDataselect(), getEvalresp(), miniseed2Stream().
- parseMiniSEED.c, unpackdata.c updated. Fixes protection stack overflow issue.
- getGaps() includes a  $0.5/\text{sampling\_rate}$  tolerance factor.
- miniseed2Stream() uses endtime from parseMiniSEED instead of calculating from the sample rate.
- Trace class now contains slots for optional metadata "latitude", "longitude", "elevation", "depth", "azimuth", "dip", "SensitivityFrequency".
- rotate2D() uses Trace class "azimuth" slot information to identify channel orientation before rotation instead of assuming lead and lag channel from trace input order.

version 1.0.8 – fixes required by ISPAQ

- Removed 'maps' and 'mapdata' from Suggested: packages.
- Changed URL syntax for FDSN web services to use "format=..." instead of "output=...".
- Fixed bug in getSNCL() so that it works when the "quality" argument is missing.

version 1.0.6 – CRAN updates required

- Removed "mode" argument from Trace.as.vector() signature.

version 1.0.4 – name change to IRISSeismic

- Name change required because 'seismic' was recently taken.
- Using explicit references for 'utils' and 'stats' package functions as this is now required for CRAN.

version 1.0.3 – cleanup for submission to CRAN

- Updated libmseed to version 2.16

version 0.2.8.0 – minor tweaks to 0.2.7

- Updated links to IRIS web services in the documentation.
- McNamaraBins() ignores bin #0 (~= DC)
- McNamaraPSD() conversion to dB occurs **after** binning, not before

version 0.2.7.0 – hilbert transform

- New hilbertFFT() function.
- New hilbert() trace method.

version 0.2.6.0 – cross correlation

- Added surfaceDistance() function.
- Added rotate2D() function.

version 0.2.5.0 – channel orientation

- Jumping to version 0.2.5 to match project milestone names.
- Added getSNCL() convenience wrapper for getDataselect() method.
- Added getDistaz() method of IrisClient.
- Added miniseed2Stream() and readMiniseedFile() functions.
- Added getRotation() method of IrisClient.

version 0.2.3.0 – cross spectrum

- Moved McNamaraPSD() from trace method to spectral utility function.
- Added spectral utility functions:
  - crossSpectrum()
  - McNamaraBins()
- All get~ methods that return dataframes now guarantee a default ordering of rows.

version 0.2.2.0 – PSD and friends

- Add dependency on pracma package.
- Use pracma::detrend() function in DDT.Trace().
- Added "increment" parameter to STALTA.Trace().
- Removed STALTA.Trace() algorithm "classic\_LR2".
- Fixed URL generation for getEvalresp() when location="".
- Added NamaraPSD.Trace() method.
- Added PSD/PDF utility functions:
  - noiseMatrix2PdfMatrix()
  - noiseModels()
  - psdDF2NoiseMatrix()
  - psdList()



- psdList2NoiseMatrix()
- psdStatistics()
- psdPlot()

version 0.2.1.1 – Bug fix release

- Removed dependency on signal, XML packages.

version 0.2.1.0 – FDSN web services

- Conversion to FDSN web services including the following new/rewritten methods: getNetwork, getStation, getChannel, getAvailability, getUnavailability
- Updated version of getEvent to return a dataframe with columns named "latitude" and "longitude" for consistency with all other web services
- Updated documentation and Rscripts to match the API changes in the conversion to FDSN web services.
- Removal of all StationXML classes in favor of storing that information in slots of the Trace class.
- Updates to Trace object slots @Sensor, @InstrumentSensitivity and @InputUnits to store information as character, numeric and character instead of StationXML classes.
- The TraceHeader@quality slot now reflects the data quality returned in the miniSEED record rather than the quality that was requested by getDataselect. (Requests with quality=B for "Best" typically return quality=M.)
- Improved STALTA.Trace() method removes experimental algorithms and now uses C++ code from package rollSeismic to calculate rolling means.
- Updated IrisClient now uses web services from <http://service.iris.edu> for the following methods: getDataselect, getEvalresp, getEvent

version 0.2.0.0

- Removed PSD methods of Stream and Trace. PSD algorithms are now part of the PSD metric.
- Improved mergeTraces.Stream() method now accepts fillMethod="fillZero".

version 0.1.9.0

- New **rollSeismic** package for fast rolling algorithms implemented in C++/Rcpp.
- New num\_spikes metric based on seismicRoll::roll\_hampel outlier detection.
- New correlation metric.
- New scripts glitchMetrics.Rscript, correlationMetric.Rscript, pressureCorrelation.Rscript
- New trace@stats@processing slot for data processing information.
- New Stream methods: mergeTraces, plot
- Improved getGaps.Stream() method properly handles initial and final gaps.
- Improved MCR error messaging.

version 0.1.8.0 – IrisClient methods getEvent and getTraveltime, improved SNR metric

version 0.1.7.0 – PSD

version 0.1.6.0 – improved errors, miniSEED parser

version 0.1.5.0 – code cleanup, improved errors, package vignette

version 0.1.4.0 – STA/LTA, upDownTimes, basic plotting

version 0.1.3.0 – SNR, memory profiling

version 0.1.2.0 – ...

version 0.1.1.0 – ...

### Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

### References

ObsPy: <http://obspy.org/>

IRIS DMC web services: <https://service.iris.edu/>

### See Also

[IrisClient-class](#), [Trace-class](#), [Stream-class](#),

### Examples

```
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient", debug=TRUE)

starttime <- as.POSIXct("2010-02-27 06:45:00", tz="GMT")
endtime <- as.POSIXct("2010-02-27 07:45:00", tz="GMT")

# Get the seismic data
result <- try(st <- getDataselect(iris,"IU","ANMO","00","BHZ",starttime,endtime))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {

# Extract the first trace, display the metadata and plot it
tr1 <- st@traces[[1]]
show(tr1@stats)
plot(tr1)
}
```

---

**basicStats***Length, Max, Mean, Median, Min and Standard Deviation*

---

**Description**

Basic statistics on the data in Trace and Stream objects.

**Usage**

```
# length(x)
# max(x, ...)
mean(x, ...)
# median(x, na.rm)
# min(x, ...)
sd(x, na.rm)
parallelLength(x)
parallelMax(x, na.rm)
parallelMean(x, na.rm)
parallelMedian(x, na.rm)
parallelMin(x, na.rm)
parallelSd(x, na.rm)
```

**Arguments**

<code>x</code>	a Trace or Stream object
<code>na.rm</code>	a logical specifying whether missing values should be removed
<code>...</code>	arguments to be passed to underlying methods, e.g. the mean function: <ul style="list-style-type: none"><li>• <code>na.rm</code> – as above (default=FALSE)</li></ul>

**Details****Trace methods**

When `x` is a Trace object, methods `length`, `max`, `mean`, `median`, `min` and `sd` operate on the data slot of the Trace and are equivalent to, e.g., `max(x@data, na.rm=FALSE)`.

**Stream methods**

When `x` is a Stream object, methods `length`, `max`, `mean`, `median`, `min` and `sd` are applied to the concatenation of data from every Trace in the Stream, treating this as a single data series.

The `parallel~` versions of these methods are available only on Stream objects and return a vector of values, one for each Trace.

By default, the Stream-method versions of these methods use `na.rm=FALSE` as there should be no missing datapoints in each Trace. The Trace methods default to `na.rm=TRUE` to accommodate merged traces where gaps have been filled with NAs.

**Value**

For the simple statistics, a single numeric value is returned or NA if the Trace or Stream has no data.

For the parallel~ versions of these methods, available on Stream objects, a numeric vector is returned of the same length as Stream@traces.

**Note**

See the R documentation on the respective base functions for further details.

The length.Stream method only counts the number of actual data values in the individual Traces in the Stream object. Missing values associated with the gaps between Traces are not counted.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2012-01-24", tz="GMT")
endtime <- as.POSIXct("2012-01-25", tz="GMT")

# Get the waveform
st <- getDataselect(iris, "AK", "PIN", "", "BHZ", starttime, endtime)

# Get the first trace and generate some statistics
tr1 <- st@traces[[1]]
length(tr1)
max(tr1)
mean(tr1)
sd(tr1)

## End(Not run)
```

---

butterworth

*Apply Butterworth filter*

---

**Description**

The butterworth method of Trace objects returns a new Trace where data in the @data slot have been modified by applying a Butterworth filter.

**Usage**

```
butterworth(x, n, low, high, type)
```

**Arguments**

x	a Trace object
n	filter order
low	frequency used in low- or stop/band-pass filters
high	frequency used in high or stop/band-pass filters
type	type of filter – 'low', 'high', 'pass' or 'stop'

**Details**

This method creates a Butterworth filter with the specified characteristics and applies it to the Trace data.

When only n and low are specified, a high pass filter is applied. When only n and high are specified, a low pass filter is applied. When n and both low and high are specified, a band pass filter is applied. To apply a band stop filter you must specify n, low, high and type='stop'

**Value**

A new Trace object is returned.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**See Also**

signal::butter, signal::filter

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

# Compare to the results in figure 2a of
#
# "Determination of New Zealand Ocean Bottom Seismometer Orientation
# via Rayleigh-Wave Polarization", Stachnik et al.
#
# http://srl.geoscienceworld.org/content/83/4/704
#
# (note: since publication, ZU.NZ19..BH1 has been renamed BH2 and ZU.NZ19..BH2 has been renamed BH1)

starttime <- as.POSIXct("2009-02-18 22:01:07",tz="GMT")
endtime <- starttime + 630
verticalLines <- starttime + seq(30,630,100)

# Get data
stZ <- getSNCL(iris,"ZU.NZ19..BHZ",starttime,endtime)
st2 <- getSNCL(iris,"ZU.NZ19..BH2",starttime,endtime)
```

```

st1 <- getSNCL(iris,"ZU.NZ19..BH1",starttime,endtime)

# Demean, Detrend, Taper
trZ <- DDT(stZ@traces[[1]],TRUE,TRUE,0.05)
tr2 <- DDT(st2@traces[[1]],TRUE,TRUE,0.05)
tr1 <- DDT(st1@traces[[1]],TRUE,TRUE,0.05)

# Bandpass filter
trZ_f <- butterworth(trZ,2,0.02,0.04,type='pass')
tr2_f <- butterworth(tr2,2,0.02,0.04,type='pass')
tr1_f <- butterworth(tr1,2,0.02,0.04,type='pass')

# 3 rows
layout(matrix(seq(3)))

# Plot
plot(trZ_f)
abline(v=verticalLines,col='gray50',lty=2)
plot(tr2_f)
abline(v=verticalLines,col='gray50',lty=2)
plot(tr1_f)
abline(v=verticalLines,col='gray50',lty=2)

# Restore default layout
layout(1)

## End(Not run)

```

---

crossSpectrum

*Cross-Spectral Analysis*


---

### Description

The `crossSpectrum()` function is based on R's `spec.pgram()` function and attempts to provide complete results of cross-spectral FFT analysis in a programmer-friendly fashion.

### Usage

```

crossSpectrum(x, spans = NULL, kernel = NULL, taper = 0.1,
              pad = 0, fast = TRUE,
              demean = FALSE, detrend = TRUE,
              na.action = stats::na.fail)

```

### Arguments

<code>x</code>	multivariate time series
<code>spans</code>	vector of odd integers giving the widths of modified Daniell smoothers to be used to smooth the periodogram
<code>kernel</code>	alternatively, a kernel smoother of class "tskernel"

taper	specifies the proportion of data to taper. A split cosine bell taper is applied to this proportion of the data at the beginning and end of the series
pad	proportion of data to pad. Zeros are added to the end of the series to increase its length by the proportion pad
fast	logical. if TRUE, pad the series to a highly composite length
demean	logical. If TRUE, subtract the mean of the series
detrend	logical. If TRUE, remove a linear trend from the series. This will also remove the mean
na.action	NA action function

### Details

The multivariate timeseries passed in as the first argument should be a union of two separate time-series with the same sampling rate created in the following manner:

```
ts1 <- ts(data1, frequency=sampling_rate)
ts2 <- ts(data2, frequency=sampling_rate)
x <- ts.union(ts1, ts2)
```

The crossSpectrum() function borrows most of its code from R's spec.pgram() function. It omits any plotting functionality and returns a programmer-friendly dataframe of all cross-spectral components generated during Fourier analysis for use in calculating transfer functions.

The naming of cross-spectral components is borrowed from the Octave version of MATLAB's pwelch() function.

### Value

A dataframe with the following columns:

freq	spectral frequencies
spec1	'two-sided' spectral amplitudes for ts1
spec2	'two-sided' spectral amplitudes for ts2
coh	magnitude squared coherence between ts1 and ts2
phase	cross-spectral phase between ts1 and ts2
Pxx	periodogram for ts1
Pyy	periodogram for ts2
Pxy	cross-periodogram for ts1 and ts2

### Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

### References

- [Octave pwelch\(\) source code](#)
- [Normalization of Power Spectral Density estimates](#)

**See Also**[McNamaraPSD](#)**Examples**

```
## Not run:
# Create a new IrisClient
iris <- new("IrisClient")

# Get seismic data
starttime <- as.POSIXct("2011-05-01", tz="GMT")
endtime <- starttime + 3600

st1 <- getDataselect(iris,"CI","PASC","00","BHZ",starttime,endtime)
st2 <- getDataselect(iris,"CI","PASC","10","BHZ",starttime,endtime)
tr1 <- st1@traces[[1]]
tr2 <- st2@traces[[1]]

# Both traces have a sampling rate of 40 Hz
sampling_rate <- tr1@stats@sampling_rate

ts1 <- ts(tr1@data,frequency=sampling_rate)
ts2 <- ts(tr2@data,frequency=sampling_rate)

# Calculate the cross spectrum
DF <- crossSpectrum(ts.union(ts1,ts2),spans=c(3,5,7,9))

# Calculate the transfer function
transferFunction <- DF$Pxy / DF$Pxx
transferAmp <- Mod(transferFunction)
transferPhase <- pracma::mod(Arg(transferFunction) * 180/pi,360)

# 2 rows
layout(matrix(seq(2)))

# Plot
plot(1/DF$freq,transferAmp,type='l',log='x',
     xlab="Period (sec)",
     main="Transfer Function Amplitude")

plot(1/DF$freq,transferPhase,type='l',log='x',
     xlab="Period (sec)", ylab="degrees",
     main="Transfer Function Phase")

# Restore default layout
layout(1)

## End(Not run)
```



---

DDT

*Apply demean, detrend, cosine taper*

---

## Description

The DDT method of Trace objects returns a new Trace where data in the @data slot have been modified. This is typically required before performing any kind of spectral analysis on the seismic trace.

## Usage

```
DDT(x, demean, detrend, taper)
```

## Arguments

x	a Trace object
demean	logical specifying whether to deman (default=TRUE)
detrend	logical specifying whether to detrend (default=TRUE)
taper	proportion of the signal to be tapered at each end (default=0.1)

## Details

Use taper=0 for no tapering.

## Value

A new Trace object is returned.

## Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

## Examples

```
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

# P-wave onset for a big quake
starttime <- as.POSIXct("2010-02-27 06:30:00", tz="GMT")
endtime <- as.POSIXct("2010-02-27 07:00:00", tz="GMT")
result <- try(st <- getDataselect(iris,"IU","ANMO","00","BHZ",starttime,endtime))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  tr <- st@traces[[1]]
  trClean <- DDT(tr,TRUE,TRUE,0.1)
  layout(matrix(seq(2)))
  plot(tr)
```

```

abline(h=0,col='gray60')
mtext("Raw",side=3,line=-2,adj=0.05,col='red')
plot(trClean)
abline(h=0,col='gray60')
mtext("Demean - Detrend - Cosine Taper",line=-2,side=3,adj=0.05,col='red')
}

# Restore default layout
layout(1)

```

---

envelope

*Envelope of a seismic signal*


---

### Description

The envelope method of Trace objects returns a Trace whose data have been replaced with the envelope of the seismic signal.

### Usage

```
envelope(x)
```

### Arguments

x                    a Trace object

### Details

Before calculating the envelope, the seismic trace is 'cleaned up' by removing the mean, the trend and by applying a cosine taper. See [DDT](#) for more details.

The seismic envelope is defined as:

$$E(t) = \sqrt{T^2(t) + H^2(t)}$$

where  $T(t)$  is the seismic trace and  $H(t)$  is the Hilbert transform of  $T(t)$ .

### Value

A Trace whose data have been replaced with the envelope of the seismic signal.

### Note

This algorithm is adapted from code in the [seewave](#) package.

### Author(s)

Jonathan Callahan <[jonathan@mazamascience.com](mailto:jonathan@mazamascience.com)>

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2010-02-27 06:00:00", tz="GMT")
endtime <- as.POSIXct("2010-02-27 09:00:00", tz="GMT")

# Get the waveform
st <- getDataselect(iris,"IU","ANMO","00","BHZ",starttime,endtime)
tr <- st@traces[[1]]

# Demean, detrend, cosine taper
tr <- DDT(tr)

# Create envelope version of the trace
trenv <- envelope(tr)

# Plot signal data and envelope data
plot(tr@data, type='l', col='gray80')
points(trenv@data, type='l', col='blue')

## End(Not run)
```

---

eventWindow

*Return a portion of a trace surrounding an event.*


---

**Description**

The eventWindow method of Trace uses the picker returned by the STALTA() method to center a window around the the event detected by the picker.

**Usage**

```
eventWindow(x, picker, threshold, windowSecs)
```

**Arguments**

x	a Trace object
picker	a picker as returned by the STALTA() method applied to this Trace
threshold	the threshold at which the picker is 'triggered'
windowSecs	the size of the window in secs

**Details**

This utility function uses the trace method triggerOnset() to determine p-wave onset followed by the slice() method to return a new Trace object of the desired size centered *near* the event onset.

When no threshold value is supplied, the default value is calculated as:

```
threshold=quantile(picker,0.999,na.rm=TRUE)
```

**Value**

A new Trace object is returned.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**See Also**

[STALTA](#), [triggerOnset](#)

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2002-04-20", tz="GMT")
endtime <- as.POSIXct("2002-04-21", tz="GMT")

# Get the waveform
st <- getDataselect(iris,"US","OXF","", "BHZ",starttime,endtime)

# Seismic signal in third trace
tr <- st@traces[[3]]

# Create a picker
picker <- STALTA(tr,3,30)
threshold <- quantile(picker,0.99999,na.rm=TRUE)

# 3 rows
layout(matrix(seq(3)))

# Plot trace and p-wave closeups
closeup1 <- eventWindow(tr,picker,threshold,3600)
closeup2 <- eventWindow(tr,picker,threshold,600)
plot(tr)
plot(closeup1,subsampling=1)
abline(v=length(closeup1)/2, col='red')
plot(closeup2,subsampling=1)
abline(v=length(closeup2)/2, col='red')

# Restore default layout
layout(1)

## End(Not run)
```

---

getAvailability	<i>Retrieve Channel metadata from IRIS DMC</i>
-----------------	--

---

### Description

The `getAvailability` method obtains channel metadata for available channels from the IRIS DMC station web service and returns it in a dataframe.

### Usage

```
getAvailability(obj, network, station, location, channel,
               starttime, endtime, includerestricted,
               latitude, longitude, minradius, maxradius)
```

### Arguments

<code>obj</code>	IrisClient object
<code>network</code>	character string with the two letter seismic network code
<code>station</code>	character string with the station code
<code>location</code>	character string with the location code
<code>channel</code>	character string with the three letter channel code
<code>starttime</code>	POSIXct class specifying the starttime (GMT)
<code>endtime</code>	POSIXct class specifying the endtime (GMT)
<code>includerestricted</code>	optional logical identifying whether to report on restricted data (default=FALSE)
<code>latitude</code>	optional latitude used when specifying a location and radius
<code>longitude</code>	optional longitude used when specifying a location and radius
<code>minradius</code>	optional minimum radius used when specifying a location and radius
<code>maxradius</code>	optional maximum radius used when specifying a location and radius

### Details

The `getAvailability` method uses the station web service to obtain data for all available channels that meet the criteria defined by the arguments and returns that data in a dataframe. Each row of the dataframe represents a unique channel-epoch. This method is equivalent to the `getChannel` method with the following additional parameters attached to the url:

```
&includeavailability=true&matchtimeseries=true
```

Each of the arguments `network`, `station`, `location` or `channel` may contain a valid code or a wildcard expression, e.g. "BH?" or "\*". Empty strings are converted to "\*". Otherwise the ascii string that is used for these values is simply inserted into the web service request URL. (For non-available channels use [getUnavailability](#).)

For more details see the [web service documentation](#).

**Value**

A dataframe with the following columns:

```
network, station, location, channel, latitude, longitude, elevation,
depth, azimuth, dip, instrument, scale, scalefreq, scaleunits,
samplerate, starttime, endtime, snclId
```

Rows are ordered by snclId.

The snclId column, eg. "US.OCWA..BHE", is generated as a convenience. It is not part of the normal return from the station web service.

**Note:** The snclId is not a unique identifier. If the time span of interest crosses an epoch boundary where instrumentation was changed then multiple records (rows) will share the same snclId.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**References**

The IRIS DMC station web service:

<https://service.iris.edu/fdsnws/station/1/>

This implementation was inspired by the functionality in the obspy `get_stations()` method.

[https://docs.obspy.org/packages/autogen/obspy.clients.fdsn.client.Client.get\\_stations.html](https://docs.obspy.org/packages/autogen/obspy.clients.fdsn.client.Client.get_stations.html)

**See Also**

[IrisClient-class](#), [getChannel](#), [getUnavailability](#)

**Examples**

```
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

# Date of Nisqually quake
starttime <- as.POSIXct("2001-02-28",tz="GMT")
endtime <- starttime + 2*24*3600

# Use getEvent web service to retrieve events in this time period
result <- try(events <- getEvent(iris,starttime,endtime,6.0))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  events

# biggest event is Nisqually
eIndex <- which(events$magnitude == max(events$magnitude))
e <- events[eIndex[1],]
```

```

# Find all BHZ channels collecting data at the time of the quake and within
# 5 degrees of the quake epicenter
result <- try(channels <- getAvailability(iris,"*","*","*", "BHZ",starttime,endtime,
                                       lat=e$latitude,long=e$longitude,maxradius=5))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  channels
}
}

```

---

getChannel

*Retrieve Channel metadata from IRIS DMC*


---

### Description

The `getChannel` method obtains channel metadata from the IRIS DMC station web service and returns it in a dataframe.

### Usage

```

getChannel(obj, network, station, location, channel,
           starttime, endtime, includerestricted,
           latitude, longitude, minradius, maxradius)

```

### Arguments

<code>obj</code>	IrisClient object
<code>network</code>	character string with the two letter seismic network code
<code>station</code>	character string with the station code
<code>location</code>	character string with the location code
<code>channel</code>	character string with the three letter channel code
<code>starttime</code>	POSIXct class specifying the starttime (GMT)
<code>endtime</code>	POSIXct class specifying the endtime (GMT)
<code>includerestricted</code>	optional logical identifying whether to report on restricted data
<code>latitude</code>	optional latitude used when specifying a location and radius
<code>longitude</code>	optional longitude used when specifying a location and radius
<code>minradius</code>	optional minimum radius used when specifying a location and radius
<code>maxradius</code>	optional maximum radius used when specifying a location and radius

## Details

The `getChannel` method uses the station web service to obtain data for all channels that meet the criteria defined by the arguments and returns that data in a dataframe. Each row of the dataframe represents a unique channel-epoch.

Each of the arguments `network`, `station`, `location` or `channel` may contain a valid code or a wildcard expression, e.g. "BH?" or "\*". Empty strings are converted to "\*". Otherwise the ascii string that is used for these values is simply inserted into the web service request URL.

For more details see the [webservice documentation](#).

## Value

A dataframe with the following columns:

```
network, station, location, channel, latitude, longitude, elevation,  
depth, azimuth, dip, instrument, scale, scalefreq, scaleunits,  
samplerate, starttime, endtime, snclId
```

Rows are ordered by `snclId`.

The `snclId` column, eg. "US.OCWA..BHE", is generated as a convenience. It is not part of the normal return from the station web service.

**Note:** The `snclIds` is not a unique identifier. If the time span of interest crosses an epoch boundary where instrumentation was changed then multiple records (rows) will share the same `snclId`.

## Author(s)

Jonathan Callahan <[jonathan@mazamascience.com](mailto:jonathan@mazamascience.com)>

## References

The IRIS DMC station webservice:

<https://service.iris.edu/fdsnws/station/1/>

This implementation was inspired by the functionality in the `obspsy` `get_stations()` method.

[https://docs.obspsy.org/packages/autogen/obspsy.clients.fdsn.client.Client.get\\_stations.html](https://docs.obspsy.org/packages/autogen/obspsy.clients.fdsn.client.Client.get_stations.html)

## See Also

[IrisClient-class](#), [getAvailability](#), [getUnavailability](#)

## Examples

```
# Open a connection to IRIS DMC webservices  
iris <- new("IrisClient")  
  
# Date of Nisqually quake  
starttime <- as.POSIXct("2001-02-28",tz="GMT")  
endtime <- starttime + 2*24*3600
```



```

# Use the getEvent web service to determine what events happened in this time period
result <- try(events <- getEvent(iris,starttime,endtime,6.0))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  events

# biggest event is Nisqually
eIndex <- which(events$magnitude == max(events$magnitude))
e <- events[eIndex[1],]
}

# Which stations in the US network are within 5 degrees of the quake epicenter?
result <- try(stations <- getStation(iris,"US","*","*","BHZ",starttime,endtime,
  lat=e$latitude,long=e$longitude,maxradius=5))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  stations
}

# Get some detailed information on any BHZ channels at the "Octopus Mountain" station
result <- try(channels <- getChannel(iris,"US","OCWA","*","BHZ",starttime,endtime))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  channels
}

```

---

getDataAvailability     *Retrieve miniseed trace extents from IRIS DMC*

---

### Description

The getDataAvailability method obtains miniseed time extents from the IRIS DMC availability web service and returns it in a dataframe.

### Usage

```

getDataAvailability(obj, network, station, location, channel,starttime, endtime,
  mergequality, mergesamplerate, mergeoverlap, mergetolerance,
  includerestricted, excludetoolarge)

```

### Arguments

obj	IrisClient object
network	character string with the two letter seismic network code
station	character string with the station code

location	character string with the location code
channel	character string with the three letter channel code
starttime	POSIXct class specifying the starttime (GMT)
endtime	POSIXct class specifying the endtime (GMT)
mergequality	optional logical identifying if timespans with differing qualities are grouped together (default=TRUE)
mergesamplerate	optional logical identifying if timespans from data with differing sample rates are grouped together (default=FALSE)
mergeoverlap	optional logical identifying if overlapping timespans are merged together (default=TRUE)
mergetolerance	optional numeric. Time spans separated by less than or equal to the mergetolerance value in seconds are merged together. To have an effect, the mergetolerance value must be larger than 1.5 times the sample period. This implements the mergegaps option in the fdsnws availability web service specification.
includerestricted	optional logical identifying whether to report on restricted data (default=FALSE)
excludetoolarge	optional logical, if TRUE sets the fdsnws availability web service option "limit=500000". default=TRUE

### Details

The `getDataAvailability` method uses the FDSNWS availability service to obtain start and end-times for all continuous trace segments in the IRIS (or other) archive for the requested network, station, location, channels and returns that data in a dataframe. Each row of the dataframe represents a unique data trace extent.

Each of the arguments `network`, `station`, `location` or `channel` may contain a valid code or a wildcard expression, e.g. "BH?" or "\*". Empty strings are converted to "\*". Otherwise the ascii string that is used for these values is simply inserted into the web service request URL.

For more details see the [web service documentation](#).

### Value

A dataframe with the following columns:

`mergequality=TRUE` and `mergesamplerate=FALSE` (defaults):

network, station, location, channel, samplerate, starttime, endtime, snclId

`mergequality=TRUE` and `mergesamplerate=TRUE`:

network, station, location, channel, starttime, endtime, snclId

`mergequality=FALSE` and `mergesamplerate=FALSE`:

network, station, location, channel, quality, samplerate, starttime, endtime, snclId

mergequality=FALSE and mergesamplerate=TRUE:

network, station, location, channel, quality, starttime, endtime, snclId

Rows are ordered by snclId.

The snclId column, eg. "US.OCWA..BHE", is generated as a convenience. It is not part of the normal return from the station web service.

### **Author(s)**

Gillian Sharer <gillian@iris.washington.edu>

### **References**

The IRIS DMC station web service:

<https://service.iris.edu/fdsnws/availability/1/> <https://service.iris.edu/ph5ws/availability/1/>

### **See Also**

[IrisClient-class](#)

### **Examples**

```
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2018-01-01", tz="GMT")
endtime <- as.POSIXct("2019-01-01", tz="GMT")
network <- "TA"
station <- "M22K"
channel <- "BHZ"

result <- try(traceList <- getDataAvailability(iris,network,station,"*",channel,starttime,endtime))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  traceList
}
```

---

getDataselect	<i>Retrieve seismic data from IRIS DMC</i>
---------------	--

---

### Description

The getDataselect method makes a request of the IRIS DMC dataselect webservice and returns a Stream object in which individual Traces have been sorted by start time.

### Usage

```
getDataselect(obj, network, station, location, channel,
              starttime, endtime, ...)
```

### Arguments

obj	IrisClient object
network	character string with the two letter seismic network code
station	character string with the station code
location	character string with the location code
channel	character string with the three letter channel code
starttime	POSIXct class specifying the starttime (GMT)
endtime	POSIXct class specifying the endtime (GMT)
...	optional arguments quality optional character string identifying the quality. IRIS webservices defaults to quality="M". repository optional character string identifying whether to exclusively search primary archive or realtime collection buffers. Acceptable values are "primary" or "realtime". If not specified, IRIS webservices defaults to both repositories. inclusiveEnd optional logical determining whether the endtime is inclusive (default = TRUE) ignoreEpoch optional logical defining behavior when multiple epochs are encountered (default = FALSE)

### Details

This is the primary method for retrieving seismic data. Data requests are made through the dataselect webservice and returned data are parsed using the internal miniseed2Stream() function.

If the location argument contains an empty string to specify a 'blank' location code, a location code of "--" will be used in the dataselect request URL. (See [dataselect documentation](#).)

If inclusiveEnd=FALSE, then getDataselect will subtract 0.000001 seconds from the endtime before passing the value to the dataselect webservice. An endtime of, e.g., as POSIXct("2016-01-03", tz="GMT") will be passed into dataselect as end=2016-01-02T23:59:59.999999. A data sample at time 2016-01-03T00:00:00 will not be returned unless inclusiveEnd=TRUE.

Error returns from the webservice will stop evaluation and generate an error message.

Sometimes the station webservice will return multiple records for the same SNCL, each with a different scale or starttime. These represent different *epochs* with potentially different metadata

parameters for the SNCL and, by default, will cause a 'Multiple epochs' error message to be generated.

Handling all possible metadata differences so that the data may be merged is beyond the scope of this package. Instead, to avoid errors, users may specify `ignoreEpoch=TRUE` in which case the very first SNCL-epoch encountered will be used and all others will be discarded.

For access to restricted data, `getDataselect` will look for system environmental variable "IrisClient\_netrc" which should point to a .netrc authentication file.

## Value

A new Stream object is returned.

## Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

## References

The IRIS DMC dataselect webservice:

<https://service.iris.edu/fdsnws/dataselect/1/>

This implementation is similar in functionality to the obspy dataselect function:

[https://docs.obspy.org/\\_modules/obspy/clients/fdsn/client.html](https://docs.obspy.org/_modules/obspy/clients/fdsn/client.html)

## See Also

[getSNCL](#), [IrisClient-class](#)

## Examples

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")
options("nanotimeFormat"="%Y-%m-%dT%H-%M-%E9S")

# Use getDataselect to request data for II.JTS.00.BHZ
starttime <- as.POSIXct("2001-02-28", tz="GMT")
endtime <- as.POSIXct("2001-03-01", tz="GMT")

st <- getDataselect(iris, "II", "JTS", "00", "BHZ", starttime, endtime,
                   inclusiveEnd=FALSE, ignoreEpoch=TRUE)

# Display structure of trace(s)

str(st)

# Plot trace
plot(st)

## End(Not run)
```

---

getDistaz	<i>Retrieve great circle distance information from IRIS DMC</i>
-----------	---

---

### Description

The getDistaz method obtains great circle distance data from the IRIS DMC distaz web service.

### Usage

```
getDistaz(obj, latitude, longitude, staLatitude, staLongitude)
```

### Arguments

obj	an IrisClient object
latitude	latitude of seismic event
longitude	longitude of seismic event
staLatitude	latitude of seismic station
staLongitude	longitude of seismic station

### Details

The distance-azimuth service will calculate the great-circle angular distance, azimuth, and back azimuth between two geographic coordinate pairs. Azimuth and back azimuth are measured clockwise from North.

### Value

A dataframe with the following columns:

```
ellipsoid.semiMajorAxis, ellipsoid.flattening, ellipsoid.name, fromlat, fromlon, tolat, tolon,
azimuth, backAzimuth, distance, distanceMeters
```

Where fromlat is the event latitude, fromlon is the event longitude, tolat is the station latitude, and tolon is the station longitude. azimuth, backAzimuth, and distance are measured in degrees. distanceMeters is distance in meters. ellipsoid.semiMajorAxis, ellipsoid.flattening, and ellipsoid.name refer to the World Geodetic System standard coordinate system version used to correct for ellipticity when converting to geocentric latitudes.

Only a single row is returned.

### Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

### References

The IRIS DMC distaz webservice:

<https://service.iris.edu/irisws/distaz/1/>

**See Also**[IrisClient-class](#)


---

getEvalresp	<i>Retrieve instrument response information from IRIS DMC</i>
-------------	---

---

**Description**

The `getEvalresp` method obtains instrument response data from the IRIS DMC `evalresp` web-service.

**Usage**

```
getEvalresp(obj, network, station, location, channel,
            time, minfreq, maxfreq, nfreq, units, output, spacing)
```

**Arguments**

<code>obj</code>	an <code>IrisClient</code> object
<code>network</code>	character string with the two letter seismic network code
<code>station</code>	character string with the station code
<code>location</code>	character string with the location code
<code>channel</code>	character string with the three letter channel code
<code>time</code>	<code>POSIXct</code> class specifying the time at which response is evaluated (GMT)
<code>minfreq</code>	optional minimum frequency at which response will be evaluated
<code>maxfreq</code>	optional maximum frequency at which response will be evaluated
<code>nfreq</code>	optional number of frequencies at which response will be evaluated
<code>units</code>	optional code specifying unit conversion
<code>output</code>	optional code specifying output type (default="fap")
<code>spacing</code>	optional code specifying spacing, accepted values are "lin" or "linear", "log" or "logarithmic" (default="log")

**Details**

The `evalresp` webservice responds to requests with data that can be used to remove instrument response from a seismic signal.

Each of `network`, `station` or `channel` should contain a valid code without wildcards. The ascii string that is used for these values is simply passed through to `evalresp`.

If the `location` argument contains an empty string to specify a 'blank' location code, a location code of "--" will be used in the `dataselect` request URL. (See [dataselect documentation](#).)

The response from `evalresp` is converted into a dataframe with rows in order of increasing frequency.

**Value**

For output="fap", a dataframe with columns named:

freq, amp, phase

For output="cs", a dataframe with columns named:

freq, real, imag

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**References**

The IRIS DMC evalresp webservice:

<https://service.iris.edu/irisws/evalresp/1/>

**See Also**

[IrisClient-class](#),

---

getEvent

*Retrieve seismic event information from the USGS NEIC*

---

**Description**

The getEvent method obtains seismic event data from the USGS NEIC event webservice.

**Usage**

```
getEvent(obj, starttime, endtime, minmag, maxmag, magtype,
         mindepth, maxdepth)
```

**Arguments**

obj	an IrisClient object
starttime	POSIXct class limiting results to events occurring after starttime (GMT)
endtime	POSIXct class limiting results to events occurring before endtime (GMT)
minmag	optional minimum magnitude
maxmag	optional maximum magnitude
magtype	optional magnitude type
mindepth	optional minimum depth (km)
maxdepth	optional maximum depth (km)



## Details

The `getEvent` method uses the event web service to obtain data for all events that meet the criteria defined by the arguments and returns that data in a dataframe. Each row of the dataframe represents a unique event.

`getEvent` calls to the IRIS event webservice now go to <https://earthquake.usgs.gov/fdsnws/event/1/>. If `obj@site` is something other than "https://service.iris.edu", `getEvent` will point to `obj@site/fdsnws/event/1/`. The event service must be able to output `format=text`.

## Value

A dataframe with the following columns:

```
eventId ,time, latitude, longitude, depth, author, cCatalog, contributor,
  contributorId, magType, magnitude, magAuthor, eventLocationName
```

Rows are ordered by time.

**NOTE:** column names are identical to the names returned from the event web service with the exception of "latitude" for "lat" and "longitude" for "lon". The longer names are used for internal consistency – all other web services return columns named "latitude" and "longitude".

## Author(s)

Jonathan Callahan <[jonathan@mazamascience.com](mailto:jonathan@mazamascience.com)>

## References

The USGS event webservice: <https://earthquake.usgs.gov/fdsnws/event/1/>

## See Also

[IrisClient-class](#),

## Examples

```
## Not run:
# NOTE: 'maps' and 'mapdata' packages must be installed
#require(maps)
#require(mapdata)

# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

# Get events > mag 5.0 over a week in June of 2012
starttime <- as.POSIXct("2012-06-21", tz="GMT")
endtime <- starttime + 3600 * 24 * 7
result <- try(events <- getEvent(iris, starttime, endtime, minmag=5.0))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
```

```

# Look at all events
print(paste(nrow(events),"earthquakes found with magnitude > 5.0"))

# Plot events on a map
#map('world')
#points(events$longitude, events$latitude, pch=16, cex=1.5, col='red')
#labels <- paste(" ", as.character(round(events$magnitude,1)), sep="")
#text(events$longitude, events$latitude, labels=labels, pos=4, cex=1.2, col='red3')
}

## End(Not run)

```

---

getGaps

*Gap analysis*


---

### Description

The `getGaps` method calculates data dropouts that occur within the requested time range associated with a `Stream`.

A `Stream` object returned by `getDataselect` contains a list of individual `Trace` objects, each of which is guaranteed to contain a continuous array of data in each `Trace@data` slot. Each `TraceHeader` also contains a `starttime` and an `endtime` defining a period of uninterrupted data collection.

Data dropouts are determined by examining the `requestedStarttime` and `requestedEndtime` slots associated with the `Stream` and the `starttime` and `endtime` slots found in the each `TraceHeader`.

### Usage

```
getGaps(x, min_gap)
```

### Arguments

<code>x</code>	Stream object
<code>min_gap</code>	minimum gap (sec) below which gaps will be ignored (default= $1/\text{sampling\_rate}$ )

### Details

This method first checks the SNCL id of each `Trace` to make sure they are identical and generates an error if they are not. Mismatches in the `sampling_rate` will also generate an error.

The data gaps (in seconds) within a `Stream` are determined and the associated `sampling_rate` is used to calculate the number of missing values in each gap. The length of the gaps and `nsamples` vectors in the returned list will be one more than the number of `Traces` (initial gap + gaps between traces + final gap).

Gaps smaller than `min_gap` are set to 0. Values of `min_gap` smaller than  $1/\text{sampling\_rate}$  will be ignored and the default value will be used instead.

Overlaps will appear as gaps with negative values.

**Value**

A list is returned with the following elements:

- gaps numeric vector of data gaps within a Stream
- nsamples number of missing samples associated with each gap

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservives
iris <- new("IrisClient")

starttime <- as.POSIXct("2012-01-24", tz="GMT")
endtime <- as.POSIXct("2012-01-25", tz="GMT")

# Get the waveform
st <- getDataselect(iris,"AK","PIN","", "BHZ",starttime,endtime)

# Save the gap analysis in a variable
gapInfo <- getGaps(st)

# See what information is availble
names(gapInfo)

# Look at a histogram of data dropouts
hist(gapInfo$nsamples, breaks=50,
      main="Data Gaps in AK.PIN..BHZ Jan 24, 2012",
      xlab="number of missing samples per gap")

## End(Not run)
```

---

getNetwork

*Retrieve Network metadata from IRIS DMC*

---

**Description**

The `getNetwork` method obtains network metadata from the IRIS DMC station web service and returns it in a dataframe.

**Usage**

```
getNetwork(obj, network, station, location, channel,
           starttime, endtime, includerestricted,
           latitude, longitude, minradius, maxradius)
```

**Arguments**

obj	IrisClient object
network	character string with the two letter seismic network code
station	character string with the station code
location	character string with the location code
channel	character string with the three letter channel code
starttime	POSIXct class specifying the starttime (GMT)
endtime	POSIXct class specifying the endtime (GMT)
includerestricted	optional logical identifying whether to report on restricted data (default=FALSE)
latitude	optional latitude used when specifying a location and radius
longitude	optional longitude used when specifying a location and radius
minradius	optional minimum radius used when specifying a location and radius
maxradius	optional maximum radius used when specifying a location and radius

**Details**

The `getNetwork` method utilizes the station web service to return data for all stations that meet the criteria defined by the arguments and returns that data in a dataframe. Each row of the dataframe represents a unique network.

Each of the arguments `network`, `station`, `location` or `channel` may contain a valid code or a wildcard expression, e.g. "BH?" or "\*". Empty strings are converted to "\*". Otherwise, the ascii string that is used for these values is simply inserted into the web service request URL.

For more details see the [web service documentation](#).

**Value**

A dataframe with the following columns:

network, description, starttime, endtime, totalstations

Rows are ordered by network.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**References**

The IRIS DMC station web service:

<https://service.iris.edu/fdsnws/station/1/>

This implementation was inspired by the functionality in the `obspsy` `get_stations()` method.

[https://docs.obspsy.org/packages/autogen/obspsy.clients.fdsn.client.Client.get\\_stations.html](https://docs.obspsy.org/packages/autogen/obspsy.clients.fdsn.client.Client.get_stations.html)

**See Also**[IrisClient-class](#)**Examples**

```

# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

# Date of Nisqually quake
starttime <- as.POSIXct("2001-02-28",tz="GMT")
endtime <- starttime + 2*24*3600

# Use the getEvent web service to determine what events happened in this time period
result <- try(events <- getEvent(iris,starttime,endtime,6.0))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  events

# biggest event is Nisqually
eIndex <- which(events$magnitude == max(events$magnitude))
e <- events[eIndex[1],]

# Which seismic networks have BHZ stations within 5 degrees of the quake epicenter?
result <- try(networks <- getNetwork(iris,"*","*","*", "BHZ",starttime,endtime,
                                     lat=e$latitude,lon=e$longitude,maxradius=5))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  networks
}
}

```

getRotation

*Retrieve rotated seismic data from IRIS DMC***Description**

The getRotation method makes a request of the IRIS DMC rotation web service and returns a list of 3 Stream objects.

**Usage**

```
getRotation(obj, network, station, location, channelSet,
            starttime, endtime, processing)
```

**Arguments**

obj	IrisClient object
network	character string with the two letter seismic network code
station	character string with the station code
location	character string with the location code
channelSet	the first two characters of the selected source channels
starttime	POSIXct class specifying the starttime (GMT)
endtime	POSIXct class specifying the endtime (GMT)
processing	optional character string with processing commands

**Details**

The rotation web service returns a triplet of seismic Streams, rotated according to the processing commands.

If the location argument contains an empty string to specify a 'blank' location code, a location code of "--" will be used in the dataselect request URL.

The processing parameter can be used to specify any type of processing supported by the rotation webs service. This string must begin with an ampersand and be ready to be appended to the request url, e.g. `processing="&components=ZRT&azimuth=23.1"`. This gives the user complete control over the number and order of processing commands. (See [rotation documentation](#).)

Error returns from the web service will stop evaluation and generate an error message.

**Value**

A list of three Stream objects is returned.

**Author(s)**

Jonathan Callahan <[jonathan@mazamascience.com](mailto:jonathan@mazamascience.com)>

**References**

The IRIS DMC rotation web service:

<https://service.iris.edu/irisws/rotation/1/>

**See Also**

[IrisClient-class](#)

---

`getSNCL`*Retrieve seismic data from IRIS DMC*

---

**Description**

The `getSNCL()` method is a convenience wrapper for the `getSNCL()` method and returns a `Stream` object in which individual `Traces` have been sorted by start time.

**Usage**

```
getSNCL(obj, sncl, starttime, endtime, ...)
```

**Arguments**

<code>obj</code>	<code>IrisClient</code> object
<code>sncl</code>	character string with the SNCL code
<code>starttime</code>	<code>POSIXct</code> class specifying the starttime (GMT)
<code>endtime</code>	<code>POSIXct</code> class specifying the endtime (GMT)
<code>...</code>	optional arguments <code>quality</code> optional character string identifying the quality. IRIS webservices defaults to <code>quality="M"</code> . <code>repository</code> optional character string identifying whether to exclusively search primary archive or realtime collection buffers. Acceptable values are "primary" or "realtime". If not specified, IRIS webservices defaults to both repositories. <code>inclusiveEnd</code> optional logical determining whether the endtime is inclusive (default = <code>TRUE</code> ) <code>ignoreEpoch</code> optional logical defining behavior when multiple epochs are encountered (default = <code>FALSE</code> )

**Details**

The SNCL argument should be ordered network-station-location channel, e.g. `IU.ANMO.00.LHZ`. This argument is split into component parts which are then used in a call to the `getSNCL()` method.

**Value**

A new `Stream` object is returned.

**Author(s)**

Jonathan Callahan <[jonathan@mazamascience.com](mailto:jonathan@mazamascience.com)>

**References**

The IRIS DMC dataselect web service:

<https://service.iris.edu/fdsnws/dataselect/1/>

**See Also**

[getDataselect](#), [IrisClient-class](#)

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

# Use getSNCL to request data for II.JTS.00.BHZ
starttime <- as.POSIXct("2001-02-28",tz="GMT")
endtime <- as.POSIXct("2001-03-01",tz="GMT")

st <- getSNCL(iris, "II.JTS.00.BHZ",starttime, endtime, quality="M",
             repository="primary",inclusiveEnd=FALSE,ignoreEpoch=TRUE)

# Display structure of trace(s)

str(st)

# Plot trace
plot(st)

## End(Not run)
```

---

getStation

*Retrieve Station metadata from IRIS DMC*

---

**Description**

The `getStation` method obtains station metadata from the IRIS DMC station web service and returns it in a dataframe.

**Usage**

```
getStation(obj, network, station, location, channel,
           starttime, endtime, includerestricted,
           latitude, longitude, minradius, maxradius)
```

**Arguments**

<code>obj</code>	IrisClient object
<code>network</code>	character string with the two letter seismic network code
<code>station</code>	character string with the station code
<code>location</code>	character string with the location code
<code>channel</code>	character string with the three letter channel code



starttime	POSIXct class specifying the starttime (GMT)
endtime	POSIXct class specifying the endtime (GMT)
includerestricted	optional logical identifying whether to report on restricted data
latitude	optional latitude used when specifying a location and radius
longitude	optional longitude used when specifying a location and radius
minradius	optional minimum radius used when specifying a location and radius
maxradius	optional maximum radius used when specifying a location and radius

### Details

The `getStation` method utilizes the station web service to obtain data for all stations that meet the criteria defined by the arguments and returns that data in a dataframe. Each row of the dataframe represents a unique station.

Each of the arguments `network`, `station`, `location` or `channel` may contain a valid code or a wildcard expression, e.g. "BH?" or "\*". Empty strings are converted to "\*". Otherwise, the ascii string that is used for these values is simply inserted into the web service request URL.

For more details see the [web service documentation](#).

### Value

A dataframe with the following columns:

`network`, `station`, `latitude`, `longitude`, `elevation`, `sitename`, `starttime`, `endtime`

Rows are ordered by `network-station`.

### Author(s)

Jonathan Callahan <[jonathan@mazamascience.com](mailto:jonathan@mazamascience.com)>

### References

The IRIS DMC station web service:

<https://service.iris.edu/fdsnws/station/1/>

This implementation was inspired by the functionality in the `obspy` `get_stations()` method.

[https://docs.obspy.org/packages/autogen/obspy.clients.fdsn.client.Client.get\\_stations.html](https://docs.obspy.org/packages/autogen/obspy.clients.fdsn.client.Client.get_stations.html)

### See Also

[IrisClient-class](#)

**Examples**

```

# Open a connection to IRIS DMC webservives
iris <- new("IrisClient")

# Date of Nisqually quake
starttime <- as.POSIXct("2001-02-28",tz="GMT")
endtime <- starttime + 2*24*3600

# Use the getEvent web service to determine what events happened in this time period
result <- try(events <- getEvent(iris,starttime,endtime,6.0))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  events

# biggest event is Nisqually
eIndex <- which(events$magnitude == max(events$magnitude))
e <- events[eIndex[1],]

# Which stations in the US network are within 5 degrees of the quake epicenter?
result <- try(stations <- getStation(iris,"US","*","*", "BHZ",starttime,endtime,
  lat=e$latitude,long=e$longitude,maxradius=5))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  stations
}
}

```

---

getTimeseries

*Retrieve seismic data from IRIS DMC*


---

**Description**

The `getTimeseries` method makes a request of the IRIS DMC timeseries webservice and returns a Stream object in which individual Traces have been sorted by start time.

**Usage**

```
getTimeseries(obj, network, station, location, channel,
  starttime, endtime,...)
```

**Arguments**

obj	IrisClient object
network	character string with the two letter seismic network code
station	character string with the station code
location	character string with the location code

channel	character string with the three letter channel code
starttime	POSIXct class specifying the starttime (GMT)
endtime	POSIXct class specifying the endtime (GMT)
...	optional arguments repository optional character string identifying whether to exclusively search primary archive or realtime collection buffers. Acceptable values are "primary" or "realtime". If not specified, IRIS webservices defaults to both repositories. processing optional character string with processing commands inclusiveEnd optional logical determining whether the endtime is inclusive (default = TRUE) ignoreEpoch optional logical defining behavior when multiple epochs are encountered (default = FALSE)

## Details

This is an alternative method for retrieving seismic data that accepts optional processing commands. Data requests are made through the `timeseries` webservice and returned data are parsed using the internal `miniseed2Stream()` function.

If the location argument contains an empty string to specify a 'blank' location code, a location code of "--" will be used in the `dataselect` request URL.

The `processing` parameter can be used to specify any type of processing supported by the `timeseries` webs service. This string must begin with an ampersand and be ready to be appended to the request url, e.g. `processing="&demean=true&taper0.2,HANNING"`. This gives the user complete control over the number and order of processing commands. (See [timeseries documentation](#).)

If `inclusiveEnd=FALSE`, then `getDataselect` will subtract 0.000001 seconds from the endtime before passing the value to the `dataselect` webservice. An endtime of, e.g., as `POSIXct("2016-01-03", tz="GMT")` will be passed into `dataselect` as `end=2016-01-02T23:59:59.999999`. A data sample at time 2016-01-03T00:00:00 will not be returned unless `inclusiveEnd=TRUE`.

Sometimes the station webservice will return multiple records for the same SNCL, each with a different scale or starttime. These represent different *epochs* with potentially different metadata parameters for the SNCL and, by default, will cause a 'Multiple epochs' error message to be generated.

Handling all possible metadata differences so that the data may be merged is beyond the scope of this package. Instead, to avoid errors, users may specify `ignoreEpoch=TRUE` in which case the very first SNCL-epoch encountered will be used and all others will be discarded.

For access to restricted data, `getDataselect` will look for system environmental variable "IrisClient\_netrc" which should point to a `.netrc` authentication file.

Error returns from the webservice will stop evaluation and generate an error message.

## Value

A new `Stream` object is returned.

## Author(s)

Jonathan Callahan <[jonathan.s.callahan@gmail.com](mailto:jonathan.s.callahan@gmail.com)>

**References**

The IRIS DMC timeseries webservice:

<https://service.iris.edu/irisws/timeseries/1/>

**See Also**

[getDataselect](#), [getSNCL](#), [IrisClient-class](#)

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices (use debug=TRUE so we can see the URLs generated)
iris <- new("IrisClient", debug=TRUE)

starttime <- as.POSIXct("2013-06-01", tz="GMT")
endtime <- starttime + 24*3600

# Get raw data and processed data
st1 <- getDataselect(iris, "IU", "ANMO", "00", "LHZ", starttime, endtime)
st2 <- getTimeSeries(iris, "IU", "ANMO", "00", "LHZ", starttime, endtime, "&demean=true&taper=0.2,HANNING")

layout(matrix(seq(2)))
plot(st1)
plot(st2)

## End(Not run)
```

---

getTraveltime

*Retrieve seismic traveltime information from IRIS DMC*

---

**Description**

The `getTraveltime` method obtains seismic traveltime data from the IRIS DMC traveltime web service and returns it in a dataframe.

**Usage**

```
getTraveltime(obj, latitude, longitude, depth, staLatitude, staLongitude)
```

**Arguments**

<code>obj</code>	an <code>IrisClient</code> object
<code>latitude</code>	latitude of seismic event
<code>longitude</code>	longitude of seismic event
<code>depth</code>	depth of seismic event
<code>staLatitude</code>	latitude of seismic station
<code>staLongitude</code>	longitude of seismic station

**Details**

The traveltime web service calculates travel-times for seismic phases using a 1-D spherical earth model.

**Value**

A dataframe with the following columns:

distance, depth, phaseName, travelTime, rayParam, takeoff, incident  
puristDistance, puristName

Rows are ordered by travelTime.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**References**

The IRIS DMC traveltime web service:

<https://service.iris.edu/irisws/traveltime/1/>

**See Also**

[IrisClient-class](#)

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

# Two days around the "Nisqually Quake"
starttime <- as.POSIXct("2001-02-27", tz="GMT")
endtime <- starttime + 3600 * 24 * 2

# Find biggest seismic event over these two days -- it's the "Nisqually"
events <- getEvent(iris, starttime, endtime, minmag=5.0)
bigOneIndex <- which(events$magnitude == max(events$magnitude))
bigOne <- events[bigOneIndex[1],]

# Find US stations that are available within an hour of the event
start <- bigOne$time
end <- start + 3600
availability <- getAvailability(iris, "US", "", "", "BHZ",
                               starttime=start, endtime=end,
                               latitude=bigOne$latitude, longitude=bigOne$longitude,
                               minradius=0, maxradius=10)

# Get the station the furthest East
```

```

minLonIndex <- which(availability$longitude == max(availability$longitude))
snclE <- availability[minLonIndex,]

# Plot the BHZ signal from this station
st <- getDataselect(iris,snclE$network,snclE$station,snclE$location,snclE$channel,
                  start,end)

# Check that there is only a single trace and then plot it
length(st@traces)
tr <- st@traces[[1]]
plot(tr, subsampling=1) # need subsampling=1 to add vertical lines with abline()

# Find travel times to this station
traveltimes <- getTraveltime(iris, bigOne$latitude, bigOne$longitude, bigOne$depth,
                           snclE$latitude, snclE$longitude)

# Look at the list
traveltimes

# mark the P and S arrival times
pArrival <- start + traveltimes$travelTime[traveltimes$phaseName=="P"]
sArrival <- start + traveltimes$travelTime[traveltimes$phaseName=="S"]
abline(v=pArrival, col='red')
abline(v=sArrival, col='blue')

## End(Not run)

```

---

getUnavailability

*Retrieve Channel metadata from IRIS DMC*


---

## Description

The `getUnavailability` method obtains metadata for channels that are not available from the IRIS DMC station web service and returns it in a dataframe.

## Usage

```

getUnavailability(obj, network, station, location, channel,
                 starttime, endtime, includerestricted,
                 latitude, longitude, minradius, maxradius)

```

## Arguments

<code>obj</code>	IrisClient object
<code>network</code>	character string with the two letter seismic network code
<code>station</code>	character string with the station code
<code>location</code>	character string with the location code
<code>channel</code>	character string with the three letter channel code

starttime	POSIXct class specifying the starttime (GMT)
endtime	POSIXct class specifying the endtime (GMT)
includerestricted	optional logical identifying whether to report on restricted data (default=FALSE)
latitude	optional latitude used when specifying a location and radius
longitude	optional longitude used when specifying a location and radius
minradius	optional minimum radius used when specifying a location and radius
maxradius	optional maximum radius used when specifying a location and radius

### Details

The `getUnavailability` method compares the results of the `getAvailability` and `getChannel` methods and returns those records found only in the output of `getChannel`.

Each of the arguments `network`, `station`, `location` or `channel` may contain a valid code or a wildcard expression, e.g. "BH?" or "\*". Empty strings are converted to "\*". Otherwise the ascii string that is used for these values is simply inserted into the web service request URL.

For more details see the [webservice documentation](#).

### Value

A dataframe with the following columns:

```
network, station, location, channel, latitude, longitude, elevation, depth,  
azimuth, dip, instrument, scale, scalefreq, scaleunits, samplerate,  
starttime, endtime
```

### Author(s)

Jonathan Callahan <[jonathan@mazamascience.com](mailto:jonathan@mazamascience.com)>

### References

The IRIS DMC station webservice:

<https://service.iris.edu/fdsnws/station/1/>

This implementation was inspired by the functionality in the `obspy get_stations()` method.

[https://docs.obspy.org/packages/autogen/obspy.clients.fdsn.client.Client.get\\_stations.html](https://docs.obspy.org/packages/autogen/obspy.clients.fdsn.client.Client.get_stations.html)

### See Also

[IrisClient-class](#), [getAvailability](#), [getChannel](#)

**Examples**

```

# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

# Date of Nisqually quake
starttime <- as.POSIXct("2001-02-28",tz="GMT")
endtime <- starttime + 2*24*3600

# Use the getEvent web service to determine what events happened in this time period
result <- try(events <- getEvent(iris,starttime,endtime,6.0))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  events

# biggest event is Nisqually
eIndex <- which(events$magnitude == max(events$magnitude))
e <- events[eIndex[1],]

# Find all BHZ channels that were NOT collecting data at the time of the quake
# and within 5 degrees of the quake epicenter (or are otherwise unavailable from IRIS).
result <- try(channels <- getUnavailability(iris,"*","*","*","BHZ",starttime,endtime,
      lat=e$latitude,long=e$longitude,maxradius=5))
if (inherits(result,"try-error")) {
  message(geterrmessage())
} else {
  channels
}
}

```

---

getUpDownTimes

*Determine times when a channel starts/stops collecting data*


---

**Description**

The getUpDownTimes method determines the on/off times for data collection within a Stream and returns a list containing these times, ignoring Traces with a duration less than min\_signal as well as data dropouts that are less than min\_gap.

**Usage**

```
getUpDownTimes(x, min_signal, min_gap)
```

**Arguments**

x	Stream object
min_signal	minimum Trace duration in seconds (default=30)
min_gap	minimum gap in seconds (default=60)



## Details

A Stream object returned by `getDataselect` contains a list of individual Trace objects, each of which is guaranteed to contain a continuous array of data in the Trace@data slot. Each Trace also contains a `starttime` and an `endtime` representing a period of uninterrupted data collection. Data dropouts are determined by first rejecting any Traces of duration less than `min_signal`. The temporal spacing between Traces is then analyzed, ignoring spaces shorter than `min_gap`.

This method first checks the SNCL id of each Trace to make sure they are identical and throws an error if they are not.

The first element returned is always the `starttime` associated the first Trace. The last element is always the `endtime` associated with the last trace. Thus, when the first element is identical to the `starttime` of the web services data request this does not necessarily mean that the channel was down before this.

**NOTE:** Even when data are complete for the duration of the requested timespan, the last element returned may be earlier than the `endtime` of the web services data request by up to a second.

## Value

A vector of POSIXct datetimes associated with on/off transitions.

## Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

## See Also

[plotUpDownTimes](#)

## Examples

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2012-01-24", tz="GMT")
endtime <- as.POSIXct("2012-01-25", tz="GMT")

# Get the waveform
st <- getDataselect(iris, "AK", "PIN", "", "BHZ", starttime, endtime)

# Determine up/down transitions, ignoring Traces < 3 min and gaps < 5 min
upDownTimes <- getUpDownTimes(st, min_signal=180, min_gap=300)

# Or just plot them directly
plotUpDownTimes(st, min_signal=180, min_gap=300)

## End(Not run)
```

---

`hilbert`*Hilbert of a seismic signal*

---

### Description

The `hilbert` method of Trace objects returns a Trace whose data have been replaced with the Hilbert transform of the seismic signal.

### Usage

```
hilbert(x)
```

### Arguments

`x` a Trace object

### Details

Before calculating the Hilbert transform, the seismic trace is 'cleaned up' by removing the mean, the trend and by applying a cosine taper. See [DDT](#) for more details.

### Value

A Trace whose data have been replaced with the Hilbert transform of the seismic signal.

### Note

This algorithm is adapted from code in the `seewave` package.

### Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

### Examples

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2010-02-27 06:00:00", tz="GMT")
endtime <- as.POSIXct("2010-02-27 09:00:00", tz="GMT")

# Get the waveform
st <- getDataselect(iris,"IU","ANMO","00","BHZ",starttime,endtime)
tr <- st@traces[[1]]

# Create Hilbert transform of the trace
trh <- hilbert(tr)
```

```
# Plot signal data and hilbert data
plot(tr@data, type='l', col='gray80')
points(trh@data, type='l', col='blue')

## End(Not run)
```

---

hilbertFFT

*Hilbert FFT*

---

## Description

The hilbertFFT function returns the complex Hilbert FFT of a timeseries signal.

## Usage

```
hilbertFFT(x)
```

## Arguments

x                    a numeric vector

## Details

This function is intended for internal use by the hilbert() and envelope() methods of Trace objects.

## Value

A complex vector containing the Hilbert FFT of x.

## Note

This algorithm is adapted from code in the **seewave** package.

## Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

## Examples

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2010-02-27 06:00:00", tz="GMT")
endtime <- as.POSIXct("2010-02-27 09:00:00", tz="GMT")

# Get the waveform
st <- getDataselect(iris, "IU", "ANMO", "00", "BHZ", starttime, endtime)
tr <- st@traces[[1]]
```

```

# Demean, detrend, cosine taper
tr <- DDT(tr)

# Calculate Hilbert FFT of the trace data
hfft <- hilbertFFT(tr@data)

# Plot signal, with Hilbert envelope
layout(1)
plot(tr@data, type='l', col='gray80', main="Signal and Envelope")
points(Mod(hfft), type='l', col='blue')

# 2 rows
layout(matrix(seq(2)))

# Show that Imaginary component of Hilbert transform has the
# original signal shifted by 90 degrees
ccf(tr@data, tr@data, lag.max=200, main="Auto-correlation of signal data")
ccf(tr@data, Im(hfft), lag.max=200, main="90 deg phase shift with Hilber transform")

# Restore default layout
layout(1)

## End(Not run)

```

---

IrisClient-class

Class "IrisClient"

---

## Description

A class for making data and metadata requests from IRIS DMC web services.

## Slots

**site:** Object of class "character": this is the first part of the url that the web service will be pointed to, defaults to `https://service.iris.edu`

**service\_type:** Object of class "character": defaults to `fdsnws`; for data retrieval from the IRIS PH5 repository, set this to `ph5ws`;

**debug:** Object of class "logical": when set to `TRUE` will cause any web service request URL to be printed

**useragent:** Object of class "character": client identification string

## Methods

**getAvailability** makes a channel request of the station web service and returns the result as a dataframe; see [getAvailability](#)

**getChannel** makes a channel request of the station web service and returns the result as a dataframe; see [getChannel](#)

- getDataAvailability** makes a channel request of the irisws availability web service and returns the result as a dataframe; see [getDataAvailability](#)
- getDataselect** makes a request of the dataselect web service and returns a Stream object; see [getDataselect](#)
- getDistaz** makes a request of the distaz web service and returns a the information as a dataframe; see [getDistaz](#)
- getEvalresp** makes a request of the instrument response web service and returns the information as a dataframe; see [getEvalresp](#)
- getEvent** makes a request of the event web service and returns the information as a dataframe, if site='https://service.iris.edu' then getEvent will direct to "https://earthquake.usgs.gov/fdsnws/event/1/query?"; see [getEvent](#)
- getNetwork** makes a network request of the station web service and returns the result as a dataframe; see [getNetwork](#)
- getSNCL**: calls the getDataselect method and returns a Stream object; see [getSNCL](#)
- getStation** makes a station request of the station web service and returns the result as a dataframe; see [getStation](#)
- getTraveltime** makes a request of the traveltime web service and returns the information as a dataframe; see [getTraveltime](#)
- getUnavailability** makes a channel request of the station web service and returns the result as a dataframe; see [getUnavailability](#)

## Note

The IrisClient object is inspired by the `clients.fdsn.client.Client` class found in the python ObsPy package (<https://docs.obspy.org/packages/autogen/obspy.clients.fdsn.client.Client.html>).

## Author(s)

Jonathan Callahan <[jonathan@mazamascience.com](mailto:jonathan@mazamascience.com)>

## Examples

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient", debug=TRUE)

starttime <- as.POSIXct("2012-01-24", tz="GMT")
endtime <- as.POSIXct("2012-01-25", tz="GMT")

# Get the waveform
st <- getDataselect(iris, "AK", "PIN", "", "BHZ", starttime, endtime)
mean(st)

## End(Not run)
```

McNamaraBins

*McNamara Binning*

---

**Description**

The McNamaraBins() function implements the binning algorithm specified in the "Data Preparation and Processing" section of [Seismic Noise Analysis System Using Power Spectral Density Probability Density Functions](#).

**Usage**

```
McNamaraBins(df, loFreq, hiFreq, alignFreq)
```

**Arguments**

df	an R dataframe object
loFreq	optional lo end of frequency binning range (default=.005)
hiFreq	optional hi end of frequency binning range (default=10)
alignFreq	optional alignment frequency for determining frequency bins (default=0.1)

**Details**

The McNamaraBins() function accepts a dataframe with an arbitrary number of columns. At least one of the columns must be named 'freq' and must contain frequency values. These frequencies will be used to assign all associated values into appropriate bins according to the McNamara algorithm: Frequencies for binning are generated at 1/8 octave intervals aligned to alignFreq. Binned values associated with each frequency bin are calculated by averaging incoming values over an entire octave centered on that frequency.

**Value**

A dataframe containing binned values is returned with the same column names as the incoming df argument.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**References**

[Seismic Noise Analysis System Using Power Spectral Density Probability Density Functions](#) (McNamara and Boaz 2005)

**See Also**

[McNamaraPSD](#)

---

McNamaraPSD                      *Power Spectral Density*

---

## Description

The McNamaraPSD() function implements the spectral density algorithm specified in the "Data Preparation and Processing" section of [Seismic Noise Analysis System Using Power Spectral Density Probability Density Functions](#).

## Usage

```
McNamaraPSD(tr, loFreq=.005, hiFreq=10, alignFreq=0.1, binned=TRUE)
```

## Arguments

tr	a Trace object
loFreq	optional lo end of frequency binning range
hiFreq	optional hi end of frequency binning range
alignFreq	optional alignment frequency for determining frequency bins
binned	logical determining whether the return spectrum is binned

## Details

This PSD algorithm is designed to be used on one to three hour segments of seismic data and will return a PSD object containing the (potentially binned) spectrum for that segment. See the [psdList](#) function for automatic segmenting of longer Stream objects.

The McNamara PSD algorithm is similar to MATLAB's `pwelch()` function and has the following steps:

1. Calculate averaged spectrum

```
# Truncate incoming segment of trace data to nearest power of 2 samples.
# Divide each truncated segment into 13 chunks with 75% overlap. The first
# chunk begins at 0/16 and ends at 4/16. The 13'th chunk begins at 12/16
# and ends at 16/16. The chunks overlap like this:
#
# 1---5---9---3---
# 2---6---0---
# 3---7---1---
# 4---8---2---
#
# Deman, detrend and taper the chunk.
# Calculate the 'one-sided' spectrum for the chunk.
#
# Average together all 13 spectra to get an averaged spectrum.
```

2. Create smoothed version of spectrum with binning

When `binned=TRUE`, McNamara style binning is turned on and a smoothed spectrum is returned that contains many fewer points than the full spectrum. When these arguments are not specified, binning is automatically turned off and the full spectrum is returned.

Frequencies for binning are generated at 1/8 octave intervals aligned to `alignFreq`. The power (dB) associated with each frequency bin is calculated by averaging over an entire octave centered on that frequency.

**Note:** The spectra returned by `McNamaraPSD()` have not had instrument correction applied. Use `getEvalresp` to get instrument correction values for specific frequencies.

3. convert binned spectra to decibels

**Value**

An R list object with the following named elements:

`freq`, `spec`, `snclq`, `starttime`, `endtime`

Elements `freq` and `spec` are numeric vectors while `snclq`, `starttime` and `endtime` are single values.

**Note**

During the binning process, an arithmetic mean is used to average together power levels in decibels. This is equivalent to averaging of power levels before conversion to dB using a geometric mean.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**References**

[Seismic Noise Analysis System Using Power Spectral Density Probability Density Functions](#) (McNamara and Boaz 2005)

**See Also**

[McNamaraBins](#), [psdList](#)

---

mergeTraces

*Merge multiple traces into a single trace*

---

**Description**

The `mergeTraces` method of `Stream` objects returns a new `Stream` where all `Traces` have been merged into a single `Trace`. Gaps between traces are replaced with values determined by the `fillMethod` parameter.



**Usage**

```
mergeTraces(x, fillMethod)
```

**Arguments**

`x` Stream object  
`fillMethod` method to use when filling gaps between Traces (default="fillNA")

**Details**

Available values for `fillMethod` include:

- `fillNA` – gaps are filled with NA (R's missing value flag)
- `fillZero` – gaps are filled with 0.0

**Value**

A new Stream object containing a single Trace is returned.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2002-04-20", tz="GMT")
endtime <- as.POSIXct("2002-04-21", tz="GMT")
st4 <- getDataselect(iris,"US","OXF","", "BHZ",starttime,endtime)
stm4 <- mergeTraces(st4)

# plot merged trace
plot(stm4@traces[[1]])
mtext(paste(length(st4@traces),"traces"), side=3, line=0.5, adj=0.05, cex=1.5)

## End(Not run)
```

---

```
mergeUpDownTimes
```

*Determine overlaps in two sets of upDownTimes.*

---

**Description**

The `mergeUpDownTimes` function determines the overlaps in two sets of times representing up/down (on/off) periods for a single or a set of channels. This function can be used to determine overall station up/down periods.

**Usage**

```
mergeUpDownTimes(udt1, udt2, bothOn)
```

**Arguments**

udt1	vector of POSIXct times representing up/down transitions
udt2	vector of POSIXct times representing up/down transitions
bothOn	logical specifying whether overlaps are determined with AND or OR (default=FALSE: udt1 OR udt2)

**Details**

When bothOn=FALSE, the default, this function returns the times of transitions from "either to neither" and back. When bothOn=TRUE, this function returns the times of transitions from "both to either" and back.

If an empty vector is passed in for udt1 or udt2 then the other vector is returned unchanged. This can be useful when merging the upDownTimes for multiple channels. See the example below.

**Value**

A vector of POSIXct datetimes associated with on/off transitions.

**Note**

The vector of times in udt1 and udt2 has no information on the values of min\_signal or min\_gap that were used to generate the timeseries. It is up to the user to make sure that the incoming vectors are appropriate for comparison. See [getUpDownTimes](#).

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**See Also**

[getUpDownTimes](#), [plotUpDownTimes](#)

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

# Three Streams, each with different upDownTimes
starttime <- as.POSIXct("2012-07-01", tz="GMT")
endtime <- as.POSIXct("2012-07-02", tz="GMT")
stE <- getDataselect(iris,"IU","XMAS","10","BHE",starttime,endtime)
stN <- getDataselect(iris,"IU","XMAS","10","BHN",starttime,endtime)
stZ <- getDataselect(iris,"IU","XMAS","10","BHZ",starttime,endtime)
udtE <- getUpDownTimes(stE)
```

```

udtN <- getUpDownTimes(stN)
udtZ <- getUpDownTimes(stZ)

udtAll <- c()
udtAny <- c()
for (udt in list(udtE, udtN, udtZ)) {
  udtAll <- mergeUpDownTimes(udtAll,udt,bothOn=TRUE)
  udtAny <- mergeUpDownTimes(udtAny,udt,bothOn=FALSE)
}

# 5 rows
layout(matrix(seq(5)))

# Plot the results
par(mar=c(3,4,3,2)) # adjust margins
plotUpDownTimes(udtE); title("BHE")
plotUpDownTimes(udtN); title("BHN")
plotUpDownTimes(udtZ); title("BHZ")
plotUpDownTimes(udtAll); title("ALL channels up")
plotUpDownTimes(udtAny); title("ANY channel up")

# Restore default layout
layout(1)

## End(Not run)

```

---

miniseed2Stream

*Convert miniSEED bytes to Stream object*


---

## Description

The `miniseed2Stream` function converts raw miniSEED bytes into a Stream object.

## Usage

```

miniseed2Stream(miniseed,url,requestedStarttime,requestedEndtime,
                sensor,scale,scalefreq,scaleunits,latitude,longitude,
                elevation,depth,azimuth,dip)

```

## Arguments

<code>miniseed</code>	a vector of raw bytes read from a miniSEED file
<code>url</code>	character source location (see <a href="#">getDataselect</a> )
<code>requestedStarttime</code>	POSIXct time associated with the requested starttime (see <a href="#">getDataselect</a> )
<code>requestedEndtime</code>	POSIXct time associated with the requested endtime (see <a href="#">getDataselect</a> )
<code>sensor</code>	character description of the Sensor type associated with this Station-Network-Channel-Location (SNCL) (see <a href="#">Trace</a> )

scale	character description of the InstrumentSensitivity associated with this SNCL (see <a href="#">Trace</a> )
scalefreq	numeric description of frequency at which the InstrumentSensitivity is correct, the SensitivityFrequency (see <a href="#">Trace</a> )
scaleunits	character description of the InputUnits associated with this SNCL (see <a href="#">Trace</a> )
latitude	numeric latitude associated with this SNCL (see <a href="#">Trace</a> )
longitude	numeric longitude associated with this SNCL (see <a href="#">Trace</a> )
elevation	numeric elevation associated with this SNCL (see <a href="#">Trace</a> )
depth	numeric depth associated with this SNCL (see <a href="#">Trace</a> )
azimuth	numeric channel azimuth associated with this SNCL (see <a href="#">Trace</a> )
dip	numeric channel dip associated with this SNCL (see <a href="#">Trace</a> )

### Details

This function takes raw bytes read in from a file or URL and converts them to a Stream object. Metadata information is optional. This function is primarily for internal use.

### Value

A Stream object.

### Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

### See Also

[readMiniseedFile](#)

---

multiplyBy

*Multiplication by a constant*

---

### Description

The multiplyBy methods of Trace and Stream objects return like objects where all @data slots have been multiplied by a constant.

### Usage

```
multiplyBy(x, y)
```

### Arguments

x	a Trace or Stream object
y	a numeric multiplier

**Value**

A new Trace or Stream object is returned.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2011-01-24", tz="GMT")
endtime <- as.POSIXct("2011-01-25", tz="GMT")

# Get the waveform
stRaw <- getDataselect(iris, "AK", "PIN", "", "BHZ", starttime, endtime)

# obtain an instrument sensitivity value with getChannel metadata)
c <- getChannel(iris, "AK", "PIN", "", "BHZ", starttime, endtime)
sensitivityValue <- c$scale

# convert raw data
st <- multiplyBy(stRaw, 1/sensitivityValue)
rmsVariance(st)

# plot trace
plot(st, ylab=c$scaleunits)

## End(Not run)
```

---

noiseMatrix2PdfMatrix *Convert matrix of PSDs to matrix of Probability Density Functions*

---

**Description**

This function converts a noiseMatrix returned by either psdList2NoiseMatrix or psdDF2NoiseMatrix into a matrix of Probability Density values as defined by McNamara and Boaz 2005.

**Usage**

```
noiseMatrix2PdfMatrix(noiseMatrix, lo, hi, binSize)
```

**Arguments**

noiseMatrix	a noiseMatrix returned from either psdList2NoiseMatrix or psdDF2NoiseMatrix
lo	lowest frequency bin (power level in dB) for the PDF y-axis (default=-200)
hi	highest frequency bin (power level in dB) for the PDF y-axis (default=-50)
binSize	size in dB of each bin (default=1)

**Details**

The McNamara and Boaz paper describes creating histograms of the discretized power levels at each frequency bin associated with a set of PSDs. The value in each cell of the PDF matrix is the fraction of the corrected PSDs that have that power level at that frequency bin.

To return a PDF matrix that matches those in the McNamara paper, use the default settings.

**Value**

A matrix is returned with one row for each power level (-250:-50 dB) and one column for each frequency bin.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**References**

[Seismic Noise Analysis System Using Power Spectral Density Probability Density Functions](#) (McNamara and Boaz 2005)

**See Also**

[McNamaraPSD](#), [psdDF2NoiseMatrix](#), [psdList](#), [psdPlot](#), [psdStatistics](#)

**Examples**

```
## Not run:
# Create a new IrisClient
iris <- new("IrisClient", debug=TRUE)

# Get seismic data
starttime <- as.POSIXct("2011-05-05", tz="GMT") # 2011.125
endtime <- starttime + 1*24*3600
st <- getDataselect(iris, "IU", "GRFO", "--", "BHE", starttime, endtime)

# Generate power spectral density for each hour long segment
psdList <- psdList(st)

# Convert into corrected "noiseMatrix"
noiseMatrix <- psdList2NoiseMatrix(psdList)

# Convert into McNamara "pdfMatrix"
pdfMatrix <- noiseMatrix2PdfMatrix(noiseMatrix)

# NOTE: Data need to be flipped and tranposed for the XY axes in the
# NOTE: image() function to match rows and columns in our pdfMatrix
# Plot pdfMatrix
image(t(pdfMatrix[, ncol(pdfMatrix):1]),
      col=c('gray90', rainbow(9)),
      axes=FALSE)
```

```
## End(Not run)
```

---

noiseModels

*Generate NHNM and NLNM noise models*

---

### Description

The noiseModels function returns the New High Noise Model and New Low Noise Model from the Peterson paper referenced below. Values are returned for the specific frequencies specified in the freq argument.

### Usage

```
noiseModels(freq)
```

### Arguments

freq            a vector of frequencies at which to generate noise model values

### Value

A list is returned with elements nhnm and nlnm containing the high and low noise models, respectively.

### Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

### References

[Observations of Modeling and Seismic Background Noise \(Peterson 1993\)](#) [Seismic Noise Analysis System Using Power Spectral Density Probability Density Functions \(McNamara and Boaz 2005\)](#)

### See Also

[psdStatistics](#),

---

psdDF2NoiseMatrix      *Apply instrument correction to PSDs*

---

### Description

The `psdDF2NoiseMatrix` function uses the `snclq` identifier associated with the first PSD in the dataframe to obtain instrument correction information at the specified frequencies from the [getEvalresp](#) web service if instrumentation correction information is not supplied as an argument. This correction is applied to every PSD in the dataframe and the now corrected PSD values are returned as a matrix.

### Usage

```
psdDF2NoiseMatrix(DF, evalresp=NULL)
```

### Arguments

DF	a dataframe of PSDs obtained from the <code>getPSDMeasurements</code> method of <code>IrisClient</code> .
evalresp	dataframe of freq, amp, phase information matching output of <code>getEvalresp</code> , optional.

### Details

This function is identical in behavior to [psdList2NoiseMatrix](#) except that the input object is a dataframe of PSD values obtained from the MUSTANG Backend Storage System.

### Value

A matrix is returned with one row for each instrument-corrected PSD and one column for each frequency bin.

### Note

The incoming dataframe is checked to make sure that it represents only a single SNCL (Station-Network-Channel-Location). An error is generated if more than one is found. However, the `psdDF` is not checked to make sure that no changes to the instrument correction happened during the time period covered by the `psdDF`. This occurs at an 'epoch' boundary when an instrument is replaced.

### Author(s)

Jonathan Callahan <[jonathan@mazamascience.com](mailto:jonathan@mazamascience.com)>

### References

[Seismic Noise Analysis System Using Power Spectral Density Probability Density Functions](#) (Mc-Namara and Boaz 2005)



**See Also**

[McNamaraPSD](#), [psdList](#), [psdList2NoiseMatrix](#), [psdPlot](#), [psdStatistics](#)

---

psdList                      *Apply McNamara PSD algorithm to a seismic signal*

---

**Description**

The `psdList` function subsets a seismic `Stream` object into a series of shorter segments with 50% overlap and uses the `McNamaraPSD` method to return a smoothed (aka binned) Power Spectral Density (PSD) for each segment.

**Usage**

```
psdList(st)
```

**Arguments**

`st`                      a `Stream` object

**Details**

A `Stream` will be subset into segments depending upon the channel identifier (`@stats@channel`) associated with this seismic data. The binning frequencies are also channel dependent as exemplified in this code extract where `Z` is the segment length in seconds:

```
alignFreq <- 0.1

if (stringr::str_detect(channel,"^L")) {
  Z <- 3 * 3600
  loFreq <- 0.001
  hiFreq <- 0.5 * tr_merged@stats@sampling_rate
} else if (stringr::str_detect(channel,"^M")) {
  Z <- 2 * 3600
  loFreq <- 0.0025
  hiFreq <- 0.5 * tr_merged@stats@sampling_rate
} else {
  Z <- 3600
  loFreq <- 0.005
  hiFreq <- 0.5 * tr_merged@stats@sampling_rate
}
```

Each new segment starts half way through the previous segment. (50% overlap)

**Value**

A list of PSD objects is returned. Each element of the list is an R list object with the following elements:

freq, spec, snclq, starttime, endtime

**Note:** Individual PSDs have not had instrument correction applied.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**References**

[Seismic Noise Analysis System Using Power Spectral Density Probability Density Functions \(McNamara and Boaz 2005\)](#)

**See Also**

[McNamaraPSD](#), [psdList2NoiseMatrix](#), [psdPlot](#), [psdStatistics](#),

**Examples**

```
## Not run:
# Create a new IrisClient
iris <- new("IrisClient", debug=TRUE)

# Get seismic data
starttime <- as.POSIXct("2011-05-05", tz="GMT") # 2011.125
endtime <- starttime + 1*24*3600
st <- getDataselect(iris,"IU","GRFO","--","BHE",starttime,endtime)

# Generate power spectral density for each hour long segment
psdList <- psdList(st)

# Plot uncorrected PSDs
period <- 1/psdList[[1]]$freq
plot(period, psdList[[1]]$spec, log='x', type='l',
      xlab="Period (Sec)", ylab="Power (dB)",
      main="Uncorrected PSDs")

for (i in seq(2:length(psdList))) {
  points(period, psdList[[i]]$spec, type='l')
}

## End(Not run)
```

---

psdList2NoiseMatrix     *Apply instrument correction to PSDs*

---

### Description

The `psdList2NoiseMatrix` function uses the `snclq` identifier associated with the first PSD in the list to obtain instrument correction information at the specified frequencies from the [getEvalresp](#) web service if instrumentation correction information is not supplied as an argument. This correction is applied to every PSD in the list and the now corrected PSD values are returned as a matrix.

### Usage

```
psdList2NoiseMatrix(psdList, evalresp=NULL)
```

### Arguments

<code>psdList</code>	a list of PSDs generated by the <code>psdList</code> function
<code>evalresp</code>	dataframe of freq, amp, phase information matching output of <code>getEvalresp</code> , optional

### Value

A matrix is returned with one row for each instrument-corrected PSD and one column for each frequency bin.

### Note

The `psdList` function generates a `psdList` from a single `Stream` of data and should thus only contain data for a single SNCL (Station-Network-Channel-Location). However, the `psdList` is not checked to make sure that no changes to the instrument correction happened during the time period covered by the `psdList`. This occurs at an 'epoch' boundary when an instrument is replaced.

### Author(s)

Jonathan Callahan <[jonathan@mazamascience.com](mailto:jonathan@mazamascience.com)>

### References

[Seismic Noise Analysis System Using Power Spectral Density Probability Density Functions](#) (McNamara and Boaz 2005)

### See Also

[McNamaraPSD](#), [psdDF2NoiseMatrix](#), [psdList](#), [psdPlot](#), [psdStatistics](#),

**Examples**

```
## Not run:
# Create a new IrisClient
iris <- new("IrisClient", debug=TRUE)

# Get seismic data
starttime <- as.POSIXct("2011-05-05", tz="GMT") # 2011.125
endtime <- starttime + 1*24*3600
st <- getDataselect(iris,"IU","GRFO","--","BHE",starttime,endtime)

# Generate power spectral density for each hour long segment
psdList <- psdList(st)

# Convert into corrected "noiseMatrix"
noiseMatrix <- psdList2NoiseMatrix(psdList)

# Plot corrected PSDs
period <- 1/psdList[[1]]$freq
plot(period, noiseMatrix[1,], log='x', type='l',
      ylim=c(-200,-50),
      xlab="Period (Sec)", ylab="Power (dB)",
      main="Corrected PSDs")

for (i in seq(2:nrow(noiseMatrix))) {
  points(period, noiseMatrix[i,], type='l')
}

## End(Not run)
```

---

psdPlot

*Generate plots from a set of PSDs*


---

**Description**

The psdPlot function is used to generate plots from the data in a psdList or psdDF dataframe.

**Usage**

```
psdPlot(PSDs, style='psd', evalresp=NULL, ylo=-200, yhi=-50, showNoiseModel=TRUE,
        showMaxMin=TRUE, showMode=TRUE, showMean=FALSE, showMedian=FALSE, ...)
```

**Arguments**

PSDs	either a list as returned by psdList or a dataframe of PSD values obtained from the BSS
style	character identifier of plot type: 'psd' plots PSD lines, 'pdf' plots the pdfMatrix
evalresp	dataframe of freq, amp, phase information matching output of getEvalresp, optional

ylo	numeric setting lower limit of plot y-axis (default=-200)
yhi	numeric setting upper limit of plot y-axis (default=-50)
showNoiseModel	logical controlling plotting of noise model lines (default=TRUE)
showMaxMin	logical controlling plotting of PSD max and min lines (default=TRUE)
showMode	logical controlling plotting of PDF mode line (default=TRUE)
showMean	logical controlling plotting of PSD mean line (default=FALSE)
showMedian	logical controlling plotting of PSD median line (default=FALSE)
...	arguments to be passed to plotting methods

### Details

The psdPlot function creates visualizations for sets of PSDs. Plots generated with style='pdf' mimic the plots presented in the McNamara paper.

### Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

### References

[Seismic Noise Analysis System Using Power Spectral Density Probability Density Functions](#) (McNamara and Boaz 2005)

### See Also

[McNamaraPSD](#), [psdList](#), [psdStatistics](#)

### Examples

```
## Not run:
# Create a new IrisClient
iris <- new("IrisClient", debug=TRUE)

# Get seismic data
starttime <- as.POSIXct("2011-05-05", tz="GMT") # 2011.125
endtime <- starttime + 1*24*3600
st <- getDataselect(iris,"IU","GRFO","--","BHE",starttime,endtime)

# Generate power spectral density for each hour long segment
psdList <- psdList(st)

# 'psd' line plot
psdPlot(psdList,style='psd',type='l',col=adjustcolor('black',0.3))

# McNamara 'pdf' plot
psdPlot(psdList,style='pdf')

## End(Not run)
```

psdStatistics

*Return statistics for a set of PSDs*

---

**Description**

The psdStatistics function calculates a variety of information associated with the incoming set of PSDs.

**Usage**

```
psdStatistics(PSDs, evalresp=NULL)
```

**Arguments**

PSDs	either a list as returned by psdList or a dataframe of PSD values obtained from the BSS
evalresp	dataframe of freq, amp, phase information matching output of getEvalresp, optional

**Value**

A list of elements:

- noiseMatrix – matrix of corrected power levels; rows=PSDs, columns=frequencies
- pdfMatrix – matrix of probability density values; rows=dB level, columns=frequencies
- freq – vector of frequencies associated statistics vectors and with matrix columns
- pdfBins – vector of power values (dB) associated with pdfMatrix rows
- max – maximum power level at each frequency
- min – minimum power level at each frequency
- mean – mean power level at each frequency
- median – median power level at each frequency
- mode – mode of power level at each frequency (obtained from pdfMatrix)
- nlnm – low noise model power level at each frequency
- nhnm – high noise model power level at each frequency
- pct\_above – percent of PSDs above the high noise model at each frequency
- pct\_below – percent of PSDS below the low noise model at each frequency

A variety of plots can be generated form the information in this list.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

## References

[Seismic Noise Analysis System Using Power Spectral Density Probability Density Functions](#) (McNamara and Boaz 2005)

## See Also

[McNamaraPSD](#), [psdList](#), [psdPlot](#)

## Examples

```
## Not run:
# Create a new IrisClient
iris <- new("IrisClient", debug=TRUE)

# Get seismic data
starttime <- as.POSIXct("2011-05-05", tz="GMT") # 2011.125
endtime <- starttime + 1*24*3600
st <- getDataselect(iris,"IU","GRFO","--","BHE",starttime,endtime)

# Generate power spectral density for each hour long segment
psdList <- psdList(st)

# Generate Statistics
stats <- psdStatistics(psdList)

# Just for fun plot
logPeriod <- log10(1/stats$freq)
plot(logPeriod,stats$max,ylim=c(-200,-50), las=1,
      xlab="log10(period)", ylab="Power (dB)",
      main="Model 'normal background noise' area and area of seismic signal.")
points(logPeriod,stats$min)

# Overlay a polygon showing the range between the noise models
x <- c(logPeriod,rev(logPeriod),logPeriod[1])
y <- c(stats$nhnm,rev(stats$nlm),stats$nhnm[1])
transparentBlack <- adjustcolor('black',0.4)
polygon(x,y,col=transparentBlack)

# Overlay a polygon showing the range of measured values
y <- c(stats$max,rev(stats$min),stats$max[1])
transparentBlue <- adjustcolor('blue',0.6)
polygon(x,y,col=transparentBlue)

## End(Not run)
```

**Description**

The readMiniseedFile function converts a raw miniSEED file into a Stream object.

**Usage**

```
readMiniseedFile(file, sensor, scale, scalefreq, scaleunits,  
                 latitude, longitude, elevation, depth, azimuth, dip)
```

**Arguments**

file	character path of a miniSEED file
sensor	character description of the Sensor associated with this Station-Network-Channel-Location (SNCL) (see <a href="#">Trace</a> )
scale	numeric description of the InstrumentSensitivity associated with this SNCL (see <a href="#">Trace</a> )
scalefreq	numeric description of frequency at which the InstrumentSensitivity is correct, the SensitivityFrequency (see <a href="#">Trace</a> )
scaleunits	character description of the InputUnits associated with this SNCL (see <a href="#">Trace</a> )
latitude	numeric latitude associated with this SNCL (see <a href="#">Trace</a> )
longitude	numeric longitude associated with this SNCL (see <a href="#">Trace</a> )
elevation	numeric elevation associated with this SNCL (see <a href="#">Trace</a> )
depth	numeric depth associated with this SNCL (see <a href="#">Trace</a> )
azimuth	numeric channel azimuth associated with this SNCL (see <a href="#">Trace</a> )
dip	numeric channel dip associated with this SNCL (see <a href="#">Trace</a> )

**Details**

This function reads in a raw miniSEED file and converts it to a Stream object. Metadata information is optional.

**Value**

A Stream object.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**See Also**

[miniseed2Stream](#)



rms

*Root Mean Square and RMS Variance***Description**

The `rms` and `rmsVariance` methods of `Trace` and `Stream` objects compute the Root Mean Square (RMS) amplitude or RMS variance of the associated data in each object. RMS variance removes the DC level from the seismic signal so that the zero line is consistent.

**Usage**

```
rms(x, na.rm)
parallelRms(x, na.rm)
rmsVariance(x, na.rm)
parallelRmsVariance(x, na.rm)
```

**Arguments**

`x` a `Trace` or `Stream` object  
`na.rm` a logical specifying whether missing values should be removed

**Details****Trace method**

The RMS amplitude of a single `Trace` is calculated as:

$$rms(x) = \sqrt{\frac{\sum_1^n (x_i)^2}{n}}$$

The RMS variance of a single `Trace` is calculated as:

$$rmsVariance(x) = \sqrt{\frac{\sum_1^n (x_i - \bar{x})^2}{n}}$$

where  $x$  is the vector of data values and  $n$  is the length of that vector.

**Stream methods**

For `Stream` objects, data from all `Traces` in the stream are first extracted and concatenated into a single numeric vector after which the algorithm is applied.

The `parallel~` version of this method is only available on `Stream` objects and returns a vector of values, one for each `Trace`.

By default, the `Stream` versions of these methods use `na.rm=FALSE` as there should be no missing datapoints in each `Trace`. The `Trace` methods default to `na.rm=TRUE` to accommodate merged traces where gaps between traces have been filled with NAs.

**Value**

A single numeric value is returned or NA if the trace has no data.

A numeric vector is returned for parallelRmsVariance.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**Examples**

```
## Not run:

# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2012-01-24", tz="GMT")
endtime <- as.POSIXct("2012-01-25", tz="GMT")

# Get the waveform
st <- getDataselect(iris,"AK","PIN","", "BHZ",starttime,endtime)

# Get the first trace and generate some statistics
tr <- st@traces[[1]]
rmsVariance(tr)

## End(Not run)
```

---

rotate2D

*Rotate horizontal components of a seismic signal*

---

**Description**

The rotate2D() function rotates the two horizontal components of a seismic signal into Radial and Transverse components returned as a list of 2 Stream objects.

**Usage**

```
rotate2D(st1, st2, angle)
```

**Arguments**

st1	horizontal Stream from a channel set (channel name usually ending in "N", "E", "1", or "2")
st2	horizontal Stream from a channel set, complementary to st1
angle	angle (degrees) of the rotation

**Details**

The rotation web service returns Radial and Transverse seismic Streams, generated by rotating st1 and st2 by angle degrees.

The rotation service uses the following transformation matrix to change the output vectors for 2-D horizontal transformations

$$M_{2D} = \begin{bmatrix} \cos\alpha & \sin\alpha \\ -\sin\alpha & \cos\alpha \end{bmatrix}$$

$$\begin{bmatrix} R \\ T \end{bmatrix} = M_{2D} \begin{bmatrix} N \\ E \end{bmatrix}$$

where :

N and E represent data from the original (horizontal) orientations.  
R and T represent the Radial and Transverse components.  
 $\alpha$  is the azimuth angle measured clockwise from north.

**Value**

A list of two Stream objects stR and stT is returned.

**Note**

N and E are determined by the Stream @stats@azimuth values. If Stream @stats@azimuth values are not defined, st1 is assumed to be N and st2 is assumed to be E. Orthogonality is also assumed to be correct.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**References**

IRIS DMC rotation web service:

<https://service.iris.edu/irisws/rotation/1/>

---

`slice`*Slice a section out of a Trace or Stream*

---

**Description**

The slice methods of Trace and Stream objects return like objects that are subsets of the original.

**Usage**

```
slice(x, starttime, endtime)
```

**Arguments**

<code>x</code>	a Trace or Stream object
<code>starttime</code>	time at which the slice should begin
<code>endtime</code>	time at which the slice should end

**Details**

The returned object will always be a subset of the `x` argument whose time range is the intersection of the original time range and the requested range. When there is no intersection or when `starttime > endtime` an error is generated.

All metadata associated with the returned Trace or Stream will reflect the new object, rather than the original.

**Value**

A new Trace or Stream object is returned.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2002-04-20", tz="GMT")
endtime <- as.POSIXct("2002-04-21", tz="GMT")

# Get the waveform
st <- getDataselect(iris,"US","OXF","", "BHZ",starttime,endtime)

# This Stream object consists of 5 Traces
length(st@traces)
```

```

# Plotting the third trace shows a small quake
plot(st@traces[[3]])

# We can slice out the hour that has the quake signal
sliceStart <- as.POSIXct("2002-04-20 10:30:00", tz="GMT")
sliceEnd <- as.POSIXct("2002-04-20 11:30:00", tz="GMT")
stSlice <- slice(st, sliceStart, sliceEnd)

# Now we only have one Trace of an hour duration
length(stSlice@traces)
stSlice@traces[[1]]@stats
# And a better look at the quake signal
plot(stSlice@traces[[1]])

## End(Not run)

```

---

STALTA

*STA/LTA*


---

### Description

The STALTA method of Trace objects applies one of several STA/LTA "first break picking" algorithms to Trace data in order to automatically detect seismic events.

### Usage

```
STALTA(x, staSecs, ltaSecs, algorithm, demean, detrend, taper, increment)
```

### Arguments

x	a Trace object
staSecs	length of the <b>S</b> hort averaging window in secs (default=3)
ltaSecs	length of the <b>L</b> ong averaging window in secs (default=30)
algorithm	algorithm to be used (default="classic_LR")
demean	boolean flag determining whether to demean the data before applying the algorithm (default=TRUE)
detrend	boolean flag determining whether to detrend the data before applying the algorithm (default=TRUE)
taper	proportion of the signal to be tapered at each end before applying the algorithm (default=0.0)
increment	the increment to use when sliding the averaging windows to the next location (default=1).

### Details

By default, this method uses the "classic\_LR" algorithm which calculates the average power in the Trace data over a short window (STA) and a long window (LTA). With this algorithm, windows are "left/right aligned" meaning that the point for which STA/LTA is calculated is at the leftmost edge of the STA window and the rightmost edge of the LTA window. The resulting STA/LTA ratio thus has the same number of points as the original data. This is a standard method of "first break picking" and can be used to identify the onset of a seismic event.

Three different algorithms are currently available:

1) algorithm="classic\_RR" This is the original STA/LTA algorithm with "right alignment".

$$STA(x_i) = \frac{1}{ns} \sum_{j=i-ns}^i x_j^2$$

$$LTA(x_i) = \frac{1}{nl} \sum_{j=i-nl}^i x_j^2$$

$$r_i = \frac{STA_i}{LTA_i}$$

[----- LTA -----\*]  
[-- STA -\*]

2) algorithm="classic\_LR" (default) This algorithm has the index at the left edge of the STA window and the right edge of the LTA window

$$STA(x_i) = \frac{1}{ns} \sum_{j=i}^{i+ns} x_j^2$$

$$LTA(x_i) = \frac{1}{nl} \sum_{j=i-nl}^i x_j^2$$

$$r_i = \frac{STA_i}{LTA_i}$$

[----- LTA -----\*]  
[\*- STA --]

3) algorithm="EarleAndShearer\_envelope"

$$STA(x_i) = \frac{1}{ns} \sum_{j=i}^{i+ns} Mod(H(x))_j$$

$$LTA(x_i) = \frac{1}{nl} \sum_{j=i-nl}^i Mod(H(x))_j$$

$$r_i = \frac{STA_i}{LTA_i}$$

```
[----- LTA -----*]
[*- STA --]
```

where  $H(x)$  is the Hilbert transform of the data and  $Mod(H(x))$  is the 'envelope' of the seismic signal. *Note that because the Hilbert transform involves performing an FFT of the data it can take significantly longer than the "classic" algorithms for longer seismic signals (>500K pts).*

### Value

A vector of values is returned of the same length as the data in the Trace.

### Note

The returned vector will contain NA near the edges of the trace where insufficient data are available to fill the windows. Additional NA values will appear for every index that is *skipped over* when the increment parameter is greater than one.

For higher resolution channels, picking an increment of  $2/\text{sampling\_rate}$  can greatly speed up processing times and still generate reasonable results.

### Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

### References

[First break picking](#) (Wikipedia)

[Automatic time-picking of first arrivals on large seismic datasets](#)

[Automatic first-breaks picking: New strategies and algorithms](#) (Sabbione and Velis 2010)

[Adaptive microseismic event detection and automatic time picking](#) (Akram and Eaton 2012)

"Characterization of Global Seismograms Using an Automatic-Picking Algorithm" Bulletin of the Seismological Society of America, Vol. 84, No. 2, pp. 366-376, April 1994 (Earle and Shearer)

### See Also

[triggerOnset](#)

### Examples

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2010-02-27",tz="GMT")
endtime <- as.POSIXct("2010-02-28",tz="GMT")

# Get the waveform
st <- getDataselect(iris,"IU","ANMO","00","BHZ",starttime,endtime)
tr <- st@traces[[1]]
picker <- STALTA(tr,3,30)
```

```

# Plot the trace and overlay the picker
plot(tr)
par(new=TRUE)
plot(picker, type='l', col='red', axes=FALSE, xlab="", ylab="")
mtext("Picker", side=1, line=-8, adj=0.05, col='red')
par(new=FALSE)

## End(Not run)

```

---

Stream-class

*Class "Stream"*


---

### Description

A Stream object containing a list of Trace objects.

### Objects from the Class

Objects are typically created by calls to [getDataselect](#).

### Slots

**url:** Object of class "character": URL request used to generate this Stream.

**requestedStarttime:** Object of class "POSIXct": starttime used when requesting data with [getDataselect](#).

**requestedEndtime:** Object of class "POSIXct": endtime used when requesting data with [getDataselect](#).

**act\_flags:** Object of class "integer": Accumulators for the act\_flags bits in each miniSEED record.

**io\_flags:** Object of class "integer": Accumulators for the io\_flags bits in each miniSEED record.

**dq\_flags:** Object of class "integer": Accumulators for the dq\_flags bits in each miniSEED record.

**timing\_qual:** Object of class "numeric": Average timing quality associated with miniSEED records.

**traces:** Object of class "list": List of Trace objects.

### Methods

**getGaps** signature(x="Stream"): returns information on data dropouts between Traces; see [getGaps](#)

**getUpDownTimes** signature(x="Stream", min\_signal="numeric", min\_gap="numeric"): returns a vector of datetimes associated with channel up/down transitions; see [getUpDownTimes](#)

**length** signature(x="Stream"): returns the total number of data points in all Traces

**max** signature(x="Stream"): returns the overall data maximum for all data in all Traces



- median** signature(x="Stream", na.rm="logical"): returns the overall data median for all data in all Traces
- mean** signature(x="Stream"): returns the overall data mean for all data in all Traces
- mergeTraces** signature(x="Stream", fillMethod="fillNA"): returns a new Stream object where all Traces have been merged into a single Trace [mergeTraces](#)
- min** signature(x="Stream"): returns the overall data minimum for all data in all Traces
- multiplyBy** signature(x="Stream", y="numeric"): returns a new Stream object where the data in every Trace have been multiplied by y; see [multiplyBy](#)
- parallelLength** signature(x="Stream"): returns a vector of data lengths, one for each Trace
- parallelMax** signature(x="Stream"): returns a vector of data maxima, one for each Trace
- parallelMedian** signature(x="Stream", na.rm="logical"): returns a vector of data medians, one for each Trace
- parallelMean** signature(x="Stream"): returns a vector of data means, one for each Trace
- parallelMin** signature(x="Stream"): returns a vector of data minima, one for each Trace
- parallelRms** signature(x="Stream"): returns a vector of RMS calculations, one for each Trace; see [rmsVariance](#)
- parallelRmsVariance** signature(x="Stream"): returns a vector of RMS variance calculations, one for each Trace; see [rmsVariance](#)
- parallelSd** signature(x="Stream", na.rm="logical"): returns a vector of standard deviation calculations, one for each Trace
- plot** signature(x="Stream"): default plot of the merged Traces in a Stream with appropriate labeling
- plotUpDownTimes** signature(x="Stream", min\_signal="numeric", min\_gap="numeric"): plots the times at which a Stream transitions from data collection to non-collection (on/off); see [getUpDownTimes](#)
- rms** signature(x="Stream"): returns the overall Root Mean Square amplitude for all data in all Traces; see [rmsVariance](#)
- rmsVariance** signature(x="Stream"): returns the overall RMS variance for all data in all Traces; see [rmsVariance](#)
- sd** signature(x="Stream", na.rm="logical"): returns the overall standard deviations for all data in all Traces
- slice** signature(x="Stream", starttime="POSIXct", endtime="POSIXct"): returns a new Stream sliced out of an existing Stream (see [slice](#))
- uniqueIds** signature(x="Stream"): returns a vector of SNCLQ identifiers, one for each Trace

## Note

The Stream object is inspired by the Stream class found in the python ObsPy package (<https://docs.obspy.org/packages/autogen/obspy.core.stream.Stream.html>).

The miniSEED flags and timing\_qual values are described in the SEED manual ([http://www.fdsn.org/seed\\_manual/SEEDManual\\_V2.4.pdf](http://www.fdsn.org/seed_manual/SEEDManual_V2.4.pdf)). The "accumulators" contain counts of the number of times each bit flag was set during the parsing of a miniSEED file. These attributes are retained primarily for assessing data quality issues within the IRIS DMC.

The following code documentation describes how each of the flags is used within miniSEED files:

```

# act_flags
# [1] Calibration signals present
# [2] Time correction applied
# [3] Beginning of an event, station trigger
# [4] End of an event, station detriquer
# [5] A positive leap second happened in this record
# [6] A negative leap second happened in this record
# [7] Event in progress
# [8] Undefined bit set

# io_flags
# [1] Station volume parity error possibly present
# [2] Long record read (possibly no problem)
# [3] Short record read (record padded)
# [4] Start of time series
# [5] End of time series
# [6] Clock locked
# [7] Undefined bit set
# [8] Undefined bit set

# dq_flags
# [1] Amplifier saturation detected
# [2] Digitizer clipping detected
# [3] Spikes detected
# [4] Glitches detected
# [5] Missing/padded data present
# [6] Telemetry synchronization error
# [7] A digital filter may be charging
# [8] Time tag is questionable

```

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**Examples**

```

## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2012-01-24", tz="GMT")
endtime <- as.POSIXct("2012-01-25", tz="GMT")

# Get the waveform
st <- getDataselect(iris,"AK","PIN","", "BHZ",starttime,endtime)
min(st)
median(st)
mean(st)
max(st)
sd(st)

```

```
rms(st)
rmsVariance(st)

## End(Not run)
```

---

surfaceDistance	<i>Earth surface distance between two points</i>
-----------------	--

---

### Description

The surfaceDistance() function calculates the distance in kilometers between any two lat-lon pairs using the Haversine equation.

### Usage

```
surfaceDistance(lat1_deg, lon1_deg, lat2_deg, lon2_deg)
```

### Arguments

lat1_deg	latitude 1 (degrees)
lon1_deg	longitude 1 (degrees)
lat2_deg	latitude 2 (degrees)
lon2_deg	longitude 2 (degrees)

### Value

Distance in kilometers

### Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

### References

[https://en.wikipedia.org/wiki/Haversine\\_formula](https://en.wikipedia.org/wiki/Haversine_formula)

Trace-class

Class "Trace"

**Description**

A Trace object containing a seismic trace – a continuous timeseries.

**Objects from the Class**

Objects occupy the traces slot of a [Stream-class](#) object and are typically populated by calls to [getDataselect](#).

**Slots**

**id:** Object of class "character": Unique "SNCL" identifier specifying the Network, Station, Location, Channel and Quality factor associated with this trace: eg. AK.PIN.VEA.M. The id is generated automatically when the trace is first created and is intended for read only.

**Sensor:** Object of class "character": Instrument name.

**InstrumentSensitivity:** Object of class "numeric": The total sensitivity for a channel, representing the complete acquisition system expressed as a scalar. Equivalent to SEED stage 0 gain.

**SensitivityFrequency:** Object of class "numeric": The frequency at which the total sensitivity is correct.

**InputUnits:** Object of class "character": The units of the data as input from the perspective of data acquisition. After correcting data for this response, these would be the resulting units.

**stats:** Object of class "TraceHeader": Container with metadata information describing the trace. (see [TraceHeader-class](#))

**data:** Object of class "numeric": Vector of data values.

**Methods**

**as.vector** signature(x="Trace"): returns the data slot; equivalent to x@data

**DDT** signature(x="Trace", demean="logical", detrend="logical", taper="numeric"): returns a new trace that has been 'cleaned up' for further processing by applying demean, detrend, and taper techniques (see [DDT](#))

**envelope** signature(x="Trace"): returns the envelope of the seismic signal (see [envelope](#))

**isDC** signature(x="Trace"): returns TRUE if trace data consist of a DC signal

**length** signature(x="Trace"): returns the length of the data; equivalent to length(x@data)

**max** signature(x="Trace"): returns the maximum value of the data; equivalent to max(x@data)

**median** signature(x="Trace", na.rm="logical"): returns the median value of the data; equivalent to median(x@data)

**mean** signature(x="Trace"): returns the mean value of the data; equivalent to mean(x@data)

**min** signature(x="Trace"): returns the minimum value of the data; equivalent to min(x@data)

- multiplyBy** signature(x="Trace", y="numeric"): returns a new Trace where the data have been multiplied by y (see [multiplyBy](#))
- plot** signature(x="Trace"): default plot of the Trace data with appropriate labeling
- rms** signature(x="Trace"): returns the Root Mean Square amplitude of the data (see [rms](#))
- rmsVariance** signature(x="Trace"): returns the RMS variance of the data (see [rmsVariance](#))
- sd** signature(x="Trace", na.rm="logical"): returns the standard deviation of the data; equivalent to sd(x@data)
- slice** signature(x="Trace", starttime="POSIXct", endtime="POSIXct"): returns a new Trace subset of an existing Trace (see [slice](#))
- STALTA** signature(x="Trace", staSecs="numeric", ltaSecs="numeric", algorithm="character", ...): returns the STALTA picker result (see [STALTA](#))
- triggerOnset** signature(x="Trace", picker="numeric", threshold="numeric", ...): returns the time or index of an event onset as determined by the STALTA picker (see [triggerOnset](#))

### Note

The Trace object is inspired by the Trace class found in the python ObsPy package (<https://docs.obspy.org/packages/autogen/obspy.core.trace.Trace.html>).

### Author(s)

Jonathan Callahan <jonathan@mazamascience.com>

### Examples

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

# Set the starttime and endtime
starttime <- as.POSIXct("2012-01-24", tz="GMT")
endtime <- as.POSIXct("2012-01-25", tz="GMT")

# Get the waveform
st <- getDataselect(iris, "AK", "PIN", "", "BHZ", starttime, endtime)

# Get the first trace and generate some statistics
tr1 <- st@traces[[1]]
min(tr1)
median(tr1)
mean(tr1)
max(tr1)
sd(tr1)
rms(tr1)
rmsVariance(tr1)

## End(Not run)
```

---

TraceHeader-class	Class "TraceHeader"
-------------------	---------------------

---

### Description

A container for metadata associated with a Trace object. Originally populated by information in the miniseed trace header; it now has the option of including additional station and channel metadata.

### Objects from the Class

Objects can be created by calls of the form `new("TraceHeader", headerList, headerLine, ...)`. The stats slot of a Trace object will contain a TraceHeader object, typically populated by a webservice request. (see [IrisClient-class](#))

### Slots

`sampling_rate`: Object of class "numeric": Sampling rate in hertz.  
`delta`: Object of class "numeric": Sample interval in seconds.  
`calib`: Object of class "numeric": Calibration factor.  
`npts`: Object of class "integer": Number of sample points.  
`network`: Object of class "character": Seismic network name.  
`location`: Object of class "character": Location code.  
`station`: Object of class "character": Station name.  
`channel`: Object of class "character": Channel code.  
`quality`: Object of class "character": Data quality code.  
`starttime`: Object of class "POSIXct": Start time.  
`endtime`: Object of class "POSIXct": End time.  
`latitude`: Object of class "numeric": Latitude.  
`longitude`: Object of class "numeric": Longitude.  
`elevation`: Object of class "numeric": Elevation.  
`depth`: Object of class "numeric": Depth.  
`azimuth`: Object of class "numeric": Azimuth.  
`dip`: Object of class "numeric": Dip.  
`processing`: Object of class "list": Information strings describing processing applied to this trace.

### Methods

**as.headerLine** signature(`obj = "TraceHeader"`): Prints out the information in the TraceHeader as an ascii header line, not including any station and channel metadata not found in the miniseed trace header, e.g.,

```
TIMESERIES LD_POTS__HHZ_M, 351 samples, 100.503 sps, \
2012-01-29T00:00:00.006000, SLIST, INTEGER, COUNTS
```

**show** signature(`object = "TraceHeader"`): Prettyprints the information in the TraceHeader

**Note**

The TraceHeader object is inspired by the Stats class found in the python ObsPy package (<https://docs.obspy.org/packages/autogen/obspy.core.trace.Stats.html>).

Retaining the ObsPy class name Stats would have generated a tremendous amount of confusion in the context of R. Instead, the name TraceHeader has been adopted. Nevertheless, the TraceHeader object still lives in the Trace@stats slot to retain as much similarity to ObsPy as possible.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2012-01-24", tz="GMT")
endtime <- as.POSIXct("2012-01-25", tz="GMT")

# Get the waveform
st <- getDataselect(iris, "AK", "PIN", "", "BHZ", starttime, endtime)

# Get the first trace and show the associated metadata
tr1 <- st@traces[[1]]
show(tr1@stats)

## End(Not run)
```

---

transferFunctionSpectra

*function to retrieve response values to use for input to the IRISMustangMetrics::transferFunctionMetric*

---

**Description**

The transferFunctionSpectra function returns a frequency-amplitude-phase response from the service.iris.edu/iris/ws/evalresp web service for a seismic Stream object using sampling\_rate to determine frequency limits. The IRISMustangMetrics::transferFunctionMetric expects this output as evalresp input.

**Usage**

```
transferFunctionSpectra(st, sampling_rate)
```

**Arguments**

st	a Stream object
sampling_rate	sample rate

**Details**

The `transferFunctionSpectra` /determines the `minfreq`, `maxfreq`, and `nfreq` for input to the `getEvalresp` function based on input sample rate. Other `getEvalresp` inputs are `units='def'` (default) and `output='fap'` (frequency-amplitude-phase).

`transferFunctionSpectra` will always call `getEvalresp` using the `service.iris.edu/irisws/evalresp` web service. The `IRISMustangMetrics::transferFunctionMetric` expects this output as `evalresp` input.

**Value**

Output is a dataframe with columns named:

`freq`, `amp`, `phase`

**Author(s)**

Mary Templeton <met@iris.washington.edu>

**See Also**

[getEvalresp](#),

**Examples**

```
## Not run:
# Create a new IrisClient
iris <- new("IrisClient", debug=TRUE)

# Get seismic data
starttime <- as.POSIXct("2011-05-05", tz="GMT")
endtime <- starttime + 1*24*3600
st <- getDataselect(iris, "IU", "GRF0", "--", "BHE", starttime, endtime)
sampling_rate <- 20

# Generate power spectral density for each hour long segment
evalresp <- transferFunctionSpectra(st, sampling_rate)

## End(Not run)
```

---

triggerOnset

*Event onset triggering*

---

**Description**

The `triggerOnset` method of `Trace` objects uses the numeric vector returned by the STALTA "first break picking" method and a user selected threshold to determine the arrival time of a seismic event.



**Usage**

```
triggerOnset(x, picker, threshold, index)
```

**Arguments**

x	a Trace object
picker	results from applying the STALTA method to this trace
threshold	optional numeric value of the threshold at which triggering should occur
index	optional logical to return the index (rather than the time) of event onset (default=FALSE)

**Details**

This method simply identifies the point at which the picker first rises above the threshold.

When no threshold is supplied, an appropriate value is calculated from the picker with:

```
threshold <- quantile(picker, 0.999, na.rm=TRUE).
```

**Value**

A single value is returned identifying the onset of the seismic event or NA if none is detected. The returned value will be a POSIXct time by default or a numeric index if index=TRUE.

**Note**

The appropriate value for the threshold will depend upon the exact STA/LTA algorithm used and the noise level in the signal.

**Author(s)**

Jonathan Callahan <jonathan@mazamascience.com>

**See Also**

[STALTA](#)

**Examples**

```
## Not run:
# Open a connection to IRIS DMC webservices
iris <- new("IrisClient")

starttime <- as.POSIXct("2010-02-27 06:00:00", tz="GMT")
endtime <- as.POSIXct("2010-02-27 09:00:00", tz="GMT")

# Get the waveform
st <- getDataselect(iris, "IU", "ANMO", "00", "BHZ", starttime, endtime)
tr <- st@traces[[1]]
picker <- STALTA(tr, 3, 30)
```

```
# Identify the onset of the event
to <- triggerOnset(tr,picker)

plot(tr)
abline(v=to, col='red', lwd=2)

## End(Not run)
```

---

unHistogram

*Histogram to Vector*

---

### **Description**

If `vec` represents a set of binned counts of incrementing values (ascending) return a vector of associated bin values with the proper count of each value. Intended for internal use.

### **Usage**

```
unHistogram(vec, startVal, incr)
```

### **Arguments**

<code>vec</code>	a histogram vector or ordered set of binned counts
<code>startVal</code>	the initial value of the first bin element
<code>incr</code>	the increment rate of each subsequent bin value

### **Value**

A vector of bin values with appropriate counts of each.

### **Author(s)**

Rob Casey <rob@iris.washington.edu>

# Index

## \* classes

IrisClient-class, 52  
Stream-class, 80  
Trace-class, 84  
TraceHeader-class, 86

## \* methods

basicStats, 11  
butterworth, 12  
DDT, 17  
envelope, 18  
eventWindow, 19  
getGaps, 34  
getUpDownTimes, 48  
hilbert, 50  
hilbertFFT, 51  
mergeTraces, 56  
multiplyBy, 60  
rms, 73  
slice, 76  
STALTA, 77  
triggerOnset, 88  
unHistogram, 90

## \* spectra

crossSpectrum, 14  
McNamaraBins, 54  
McNamaraPSD, 55  
noiseMatrix2PdfMatrix, 61  
noiseModels, 63  
psdDF2NoiseMatrix, 64  
psdList, 65  
psdList2NoiseMatrix, 67  
psdPlot, 68  
psdStatistics, 70  
transferFunctionSpectra, 87

## \* webservice

getAvailability, 21  
getChannel, 23  
getDataAvailability, 25  
getDataselect, 28

getDistaz, 30  
getEvalresp, 31  
getEvent, 32  
getNetwork, 35  
getRotation, 37  
getSNCL, 39  
getStation, 40  
getTimeseries, 42  
getTraveltime, 44  
getUnavailability, 46

as.headerLine (TraceHeader-class), 86  
as.headerLine, TraceHeader-method  
(TraceHeader-class), 86  
as.vector, Trace-method (Trace-class), 84

basicStats, 11  
butterworth, 12  
butterworth, Trace, numeric, missing, numeric, missing-method  
(butterworth), 12  
butterworth, Trace, numeric, numeric, missing, missing-method  
(butterworth), 12  
butterworth, Trace, numeric, numeric, numeric, character-method  
(butterworth), 12  
butterworth, Trace, numeric, numeric, numeric, missing-method  
(butterworth), 12

crossSpectrum, 14

DDT, 17, 18, 50, 84  
DDT, Trace, logical, logical, numeric-method  
(DDT), 17  
DDT, Trace, missing, missing, missing-method  
(DDT), 17

envelope, 18, 84  
envelope, Trace-method (envelope), 18  
eventWindow, 19  
eventWindow, Trace, numeric, missing, missing-method  
(eventWindow), 19

- eventWindow, Trace, numeric, missing, numeric-method  
     (eventWindow), 19
- eventWindow, Trace, numeric, numeric, missing-method  
     (eventWindow), 19
- eventWindow, Trace, numeric, numeric, numeric-method  
     (eventWindow), 19
- getAvailability, 21, 24, 47, 52
- getAvailability, IrisClient, character, character, character, character, character, POSIXct, POSIXct, logical-method  
     (getAvailability), 21
- getAvailability, IrisClient, character, character, character, character, character, POSIXct, POSIXct, missing-method  
     (getAvailability), 21
- getChannel, 22, 23, 47, 52
- getChannel, IrisClient, character, character, character, character, character, POSIXct, POSIXct, logical-method  
     (getChannel), 23
- getChannel, IrisClient, character, character, character, character, character, POSIXct, POSIXct, missing-method  
     (getChannel), 23
- getDataAvailability, 25, 53
- getDataAvailability, IrisClient, character, character, character, character, character, POSIXct, POSIXct-method  
     (getDataAvailability), 25
- getDataselect, 28, 34, 40, 44, 49, 53, 59, 80, 84
- getDataselect, IrisClient, character, character, character, character, character, POSIXct, POSIXct-method  
     (getDataselect), 28
- getDistaz, 30, 53
- getDistaz, IrisClient, numeric, numeric, numeric, numeric-method  
     (getDistaz), 30
- getEvalresp, 31, 53, 56, 64, 67, 88
- getEvalresp, IrisClient, character, character, character, character, character, POSIXct, POSIXct-method  
     (getEvalresp), 31
- getEvent, 32, 53
- getEvent, IrisClient, POSIXct, POSIXct-method  
     (getEvent), 32
- getGaps, 34, 80
- getGaps, Stream, missing-method  
     (getGaps), 34
- getGaps, Stream, numeric-method  
     (getGaps), 34
- getNetwork, 35, 53
- getNetwork, IrisClient, character, character, character, character, character, POSIXct, POSIXct, logical-method  
     (getNetwork), 35
- getNetwork, IrisClient, character, character, character, character, character, POSIXct, POSIXct, missing-method  
     (getNetwork), 35
- getRotation, 37
- getRotation, IrisClient, character, character, character, character, character, POSIXct, POSIXct, character-method  
     (getRotation), 37
- getSNCL, 29, 39, 44, 53
- getSNCL, IrisClient, character, POSIXct, POSIXct-method  
     (getSNCL), 39
- getStation, 40, 53
- getStation, IrisClient, character, character, character, character, character, POSIXct, POSIXct, logical-method  
     (getStation), 40
- getStation, IrisClient, character, character, character, character, character, POSIXct, POSIXct, missing-method  
     (getStation), 40
- getTimeseries, 42
- getTimeseries, IrisClient, character, character, character, character, character, POSIXct, POSIXct, logical-method  
     (getTimeseries), 42
- getTraveltime, 41, 53
- getTraveltime, IrisClient, numeric, numeric, numeric, numeric, numeric, numeric, numeric, numeric-method  
     (getTraveltime), 41
- getUnavailability, 21, 22, 24, 46, 53
- getUnavailability, IrisClient, character, character, character, character, character, POSIXct, POSIXct, logical-method  
     (getUnavailability), 46
- getUnavailability, IrisClient, character, character, character, character, character, POSIXct, POSIXct, missing-method  
     (getUnavailability), 46
- getUpDownTimes, 48, 58, 80, 81
- getUpDownTimes, Stream, missing, missing-method  
     (getUpDownTimes), 48
- getUpDownTimes, Stream, numeric, numeric-method  
     (getUpDownTimes), 48
- hilbert, Trace-method (hilbert), 50
- hilbertFFT, 51
- initialize, IrisClient-method  
     (IrisClient-class), 52
- initialize, TraceHeader-method (TraceHeader-class), 84
- initialize, TraceHeader-method  
     (TraceHeader-class), 86
- IrisClient-class, 52, 86
- IRISseismic (IRISseismic-package), 3
- IRISseismic-package, 3
- isDC (Trace-class), 84
- isDC, Trace-method (Trace-class), 84
- length (basicStats), 11
- length, character, character, POSIXct, POSIXct, logical-method  
     (basicStats), 11
- length, Trace-method (basicStats), 11
- max (basicStats), 11
- max, Stream-method (basicStats), 11
- McNamaraBins, 54, 56
- McNamaraPSD, 16, 54, 55, 62, 65–67, 69, 71
- mean (basicStats), 11
- mean, Stream-method (basicStats), 11

- mean, Trace-method (basicStats), 11
- median (basicStats), 11
- median, Stream, logical-method (basicStats), 11
- median, Stream, missing-method (basicStats), 11
- median, Trace, logical-method (basicStats), 11
- median, Trace, missing-method (basicStats), 11
- mergeTraces, 56, 81
- mergeTraces, Stream, character-method (mergeTraces), 56
- mergeTraces, Stream, missing-method (mergeTraces), 56
- mergeUpDownTimes, 57
- mergeUpDownTimes, NULL, POSIXct, logical-method (mergeUpDownTimes), 57
- mergeUpDownTimes, NULL, POSIXct, missing-method (mergeUpDownTimes), 57
- mergeUpDownTimes, POSIXct, NULL, logical-method (mergeUpDownTimes), 57
- mergeUpDownTimes, POSIXct, NULL, missing-method (mergeUpDownTimes), 57
- mergeUpDownTimes, POSIXct, POSIXct, logical-method (mergeUpDownTimes), 57
- mergeUpDownTimes, POSIXct, POSIXct, missing-method (mergeUpDownTimes), 57
- min (basicStats), 11
- min, Stream-method (basicStats), 11
- min, Trace-method (basicStats), 11
- miniseed2Stream, 59, 72
- multiplyBy, 60, 81, 85
- multiplyBy, Stream, numeric-method (multiplyBy), 60
- multiplyBy, Trace, numeric-method (multiplyBy), 60
  
- noiseMatrix2PdfMatrix, 61
- noiseModels, 63
  
- parallelLength (basicStats), 11
- parallelLength, Stream-method (basicStats), 11
- parallelMax (basicStats), 11
- parallelMax, Stream, logical-method (basicStats), 11
- parallelMax, Stream, missing-method (basicStats), 11
- parallelMean (basicStats), 11
- parallelMean, Stream, logical-method (basicStats), 11
- parallelMean, Stream, missing-method (basicStats), 11
- parallelMedian (basicStats), 11
- parallelMedian, Stream, logical-method (basicStats), 11
- parallelMedian, Stream, missing-method (basicStats), 11
- parallelMin (basicStats), 11
- parallelMin, Stream, logical-method (basicStats), 11
- parallelMin, Stream, missing-method (basicStats), 11
- parallelRms (rms), 73
- parallelRmsVariance (rms), 73
- parallelRmsVariance, Stream, logical-method (basicStats), 11
- parallelRmsVariance, Stream, missing-method (basicStats), 11
- parallelSd (basicStats), 11
- parallelSd, Stream, logical-method (basicStats), 11
- parallelSd, Stream, missing-method (basicStats), 11
- plot, Stream-method (Stream-class), 80
- plot, Trace-method (Trace-class), 84
- plotUpDownTimes, 49, 58
- plotUpDownTimes (Stream-class), 80
- plotUpDownTimes, POSIXct, missing, missing-method (Stream-class), 80
- plotUpDownTimes, POSIXct, missing, numeric-method (Stream-class), 80
- plotUpDownTimes, POSIXct, numeric, missing-method (Stream-class), 80
- plotUpDownTimes, POSIXct, numeric, numeric-method (Stream-class), 80
- plotUpDownTimes, Stream, missing, missing-method (Stream-class), 80
- plotUpDownTimes, Stream, missing, numeric-method (Stream-class), 80
- plotUpDownTimes, Stream, numeric, missing-method (Stream-class), 80
- plotUpDownTimes, Stream, numeric, numeric-method (Stream-class), 80
- psdDF2NoiseMatrix, 62, 64, 67
- psdList, 55, 56, 62, 65, 65, 67, 69, 71

- psdList2NoiseMatrix, [64–66](#), [67](#)
- psdPlot, [62](#), [65–67](#), [68](#), [71](#)
- psdStatistics, [62](#), [63](#), [65–67](#), [69](#), [70](#)
- readMiniseedFile, [60](#), [71](#)
- rms, [73](#), [85](#)
- rms, Stream, logical-method (basicStats), [11](#)
- rms, Stream, missing-method (basicStats), [11](#)
- rms, Trace, logical-method (rms), [73](#)
- rms, Trace, missing-method (rms), [73](#)
- rmsVariance, [81](#), [85](#)
- rmsVariance (rms), [73](#)
- rmsVariance, Stream, logical-method (basicStats), [11](#)
- rmsVariance, Stream, missing-method (basicStats), [11](#)
- rmsVariance, Trace, logical-method (rms), [73](#)
- rmsVariance, Trace, missing-method (rms), [73](#)
- rotate2D, [74](#)
- sd (basicStats), [11](#)
- sd, Stream, logical-method (basicStats), [11](#)
- sd, Stream, missing-method (basicStats), [11](#)
- sd, Trace, logical-method (basicStats), [11](#)
- sd, Trace, missing-method (basicStats), [11](#)
- show, TraceHeader-method (TraceHeader-class), [86](#)
- slice, [76](#), [81](#), [85](#)
- slice, Stream, POSIXct, POSIXct-method (Stream-class), [80](#)
- slice, Trace, POSIXct, POSIXct-method (slice), [76](#)
- STALTA, [20](#), [77](#), [85](#), [89](#)
- STALTA, Trace, missing, missing, missing, missing, missing, missing, missing-method (STALTA), [77](#)
- STALTA, Trace, numeric, numeric, character, logical, logical, numeric, numeric-method (STALTA), [77](#)
- STALTA, Trace, numeric, numeric, character, missing, missing, missing, missing-method (STALTA), [77](#)
- STALTA, Trace, numeric, numeric, missing, missing, missing, missing, missing-method (STALTA), [77](#)
- Stream (Stream-class), [80](#)
- Stream-class, [80](#), [84](#)
- surfaceDistance, [83](#)
- Trace, [59](#), [60](#), [72](#)
- Trace (Trace-class), [84](#)
- Trace-class, [84](#)
- TraceHeader (TraceHeader-class), [86](#)
- TraceHeader-class, [84](#), [86](#)
- transferFunctionSpectra, [87](#)
- triggerOnset, [20](#), [79](#), [85](#), [88](#)
- triggerOnset, Trace, numeric-method (triggerOnset), [88](#)
- unHistogram, [90](#)
- uniqueIds (Stream-class), [80](#)
- uniqueIds, Stream-method (Stream-class), [80](#)