

# Package ‘keyATM’

April 24, 2024

**Version** 0.5.2

**Title** Keyword Assisted Topic Models

**Description**

Fits keyword assisted topic models (keyATM) using collapsed Gibbs samplers. The keyATM combines the latent dirichlet allocation (LDA) models with a small number of keywords selected by researchers in order to improve the interpretability and topic classification of the LDA. The keyATM can also incorporate covariates and directly model time trends. The keyATM is proposed in Eshima, Imai, and Sasaki (2024) <[doi:10.1111/ajps.12779](https://doi.org/10.1111/ajps.12779)>.

**License** GPL-3

**Depends** R (>= 4.0)

**Imports** Rcpp (>= 1.0.7), cli (>= 3.6.1), dplyr (>= 1.1.0), fastmap, future.apply, fs (>= 1.6.0), ggplot2 (>= 3.4.0), ggrepel, magrittr, Matrix, matrixNormal (>= 0.1.0), MASS, pgdraw, purrr (>= 1.0.0), quanteda (>= 3.3.0), rlang (>= 1.1.0), stringr, tibble, tidyr (>= 1.0.0), tidysselect (>= 1.2.0)

**LinkingTo** Rcpp, RcppEigen, cli

**Suggests** readtext, stats, testthat (>= 3.1.5)

**URL** <https://keyatm.github.io/keyATM/>

**Encoding** UTF-8

**BugReports** <https://github.com/keyATM/keyATM/issues>

**LazyData** TRUE

**RoxygenNote** 7.2.3

**SystemRequirements** C++17

**NeedsCompilation** yes

**Author** Shusei Eshima [aut, cre] (<<https://orcid.org/0000-0003-3613-4046>>),  
Tomoya Sasaki [aut],  
Kosuke Imai [aut],  
Chung-hong Chan [ctb] (<<https://orcid.org/0000-0002-6232-7530>>),  
Romain François [ctb] (<<https://orcid.org/0000-0002-2444-4226>>),  
William Lowe [ctb],  
Seo-young Silvia Kim [ctb] (<<https://orcid.org/0000-0002-8801-9210>>)

**Maintainer** Shusei Eshima <shuseieshima@gmail.com>

**Repository** CRAN

**Date/Publication** 2024-04-24 14:50:06 UTC

## R topics documented:

keyATM-package . . . . .	2
by_strata_DocTopic . . . . .	3
by_strata_TopicWord . . . . .	4
covariates_get . . . . .	4
covariates_info . . . . .	5
keyATM . . . . .	5
keyATMvb . . . . .	8
keyATM_data_bills . . . . .	9
keyATM_read . . . . .	9
multiPGreg . . . . .	10
plot.strata_doctopic . . . . .	11
plot_alpha . . . . .	12
plot_modelfit . . . . .	13
plot_pi . . . . .	13
plot_timetrend . . . . .	14
plot_topicprop . . . . .	15
predict.keyATM_output . . . . .	16
read_keywords . . . . .	17
save_fig . . . . .	18
semantic_coherence . . . . .	19
top_docs . . . . .	19
top_topics . . . . .	20
top_words . . . . .	20
values_fig . . . . .	21
visualize_keywords . . . . .	21
weightedLDA . . . . .	22
<b>Index</b>	<b>24</b>

---

keyATM-package

*Keyword Assisted Topic Models*

---

### Description

The implementation of keyATM models.

**Author(s)**

**Maintainer:** Shusei Eshima <shuseieshima@gmail.com> ([ORCID](#))

Authors:

- Tomoya Sasaki <tomoyas@mit.edu>
- Kosuke Imai <imai@harvard.edu>

Other contributors:

- Chung-hong Chan <chainsawtiney@gmail.com> ([ORCID](#)) [contributor]
- Romain François ([ORCID](#)) [contributor]
- William Lowe <wlowe@princeton.edu> [contributor]
- Seo-young Silvia Kim <sy.silvia.kim@gmail.com> ([ORCID](#)) [contributor]

**See Also**

Useful links:

- <https://keyatm.github.io/keyATM/>
- Report bugs at <https://github.com/keyATM/keyATM/issues>

---

by\_strata\_DocTopic      *Estimate document-topic distribution by strata (for covariate models)*

---

**Description**

Estimate document-topic distribution by strata (for covariate models)

**Usage**

```
by_strata_DocTopic(x, by_var, labels, by_values = NULL, ...)
```

**Arguments**

x	the output from the covariate keyATM model (see <a href="#">keyATM()</a> ).
by_var	character. The name of the variable to use.
labels	character. The labels for the values specified in by_var (ascending order).
by_values	numeric. Specific values for by_var, ordered from small to large. If it is not specified, all values in by_var will be used.
...	other arguments passed on to the <a href="#">predict.keyATM_output()</a> function.

**Value**

strata\_topicword object (a list).

---

by\_strata\_TopicWord     *Estimate subsetted topic-word distribution*

---

**Description**

Estimate subsetted topic-word distribution

**Usage**

```
by_strata_TopicWord(x, keyATM_docs, by)
```

**Arguments**

x                    the output from a keyATM model (see [keyATM\(\)](#)).  
keyATM\_docs        an object generated by [keyATM\\_read\(\)](#).  
by                   a vector whose length is the number of documents.

**Value**

strata\_topicword object (a list).

---

covariates\_get        *Return covariates used in the iteration*

---

**Description**

Return covariates used in the iteration

**Usage**

```
covariates_get(x)
```

**Arguments**

x                    the output from the covariate keyATM model (see [keyATM\(\)](#))

---

covariates_info	<i>Show covariates information</i>
-----------------	------------------------------------

---

**Description**

Show covariates information

**Usage**

```
covariates_info(x)
```

**Arguments**

x                    the output from the covariate keyATM model (see [keyATM\(\)](#)).

---

keyATM	<i>keyATM main function</i>
--------	-----------------------------

---

**Description**

Fit keyATM models.

**Usage**

```
keyATM(
  docs,
  model,
  no_keyword_topics,
  keywords = list(),
  model_settings = list(),
  priors = list(),
  options = list(),
  keep = c()
)
```

**Arguments**

docs                texts read via [keyATM\\_read\(\)](#).

model              keyATM model: base, covariates, and dynamic.

no\_keyword\_topics    the number of regular topics.

keywords            a list of keywords.

model\_settings    a list of model specific settings (details are in the online documentation).

priors              a list of priors of parameters.

options	<p>a list of options</p> <ul style="list-style-type: none"> <li>• <b>seed</b>: A numeric value for random seed. If it is not provided, the package randomly selects a seed.</li> <li>• <b>iterations</b>: An integer. Number of iterations. Default is 1500.</li> <li>• <b>verbose</b>: If TRUE, it prints loglikelihood and perplexity. Default is FALSE.</li> <li>• <b>llk_per</b>: An integer. If the value is <math>j</math> <b>keyATM</b> stores loglikelihood and perplexity every <math>j</math> iteration. Default value is 10 per iterations</li> <li>• <b>use_weights</b>: If TRUE use weight. Default is TRUE.</li> <li>• <b>weights_type</b>: There are four types of weights. Weights based on the information theory (<code>information-theory</code>) and inverse frequency (<code>inv-freq</code>) and normalized versions of them (<code>information-theory-normalized</code> and <code>inv-freq-normalized</code>). Default is <code>information-theory</code>.</li> <li>• <b>prune</b>: If TRUE rume keywords that do not appear in the corpus. Default is TRUE.</li> <li>• <b>store_theta</b>: If TRUE or 1, it stores <math>\theta</math> (document-topic distribution) for the iteration specified by thinning. Default is FALSE (same as 0).</li> <li>• <b>store_pi</b>: If TRUE or 1, it stores <math>\pi</math> (the probability of using keyword topic word distribution) for the iteration specified by thinning. Default is FALSE (same as 0).</li> <li>• <b>thinning</b>: An integer. If the value is <math>j</math> <b>keyATM</b> stores following parameters every <math>j</math> iteration. The default is 5. <ul style="list-style-type: none"> <li>– <i>theta</i>: For all models. If <code>store_theta</code> is TRUE document-level topic assignment is stored (sufficient statistics to calculate document-topic distributions <code>theta</code>).</li> <li>– <i>alpha</i>: For the base and dynamic models. In the base model <code>alpha</code> is shared across all documents whereas each state has different <code>alpha</code> in the dynamic model.</li> <li>– <i>lambda</i>: coefficients in the covariate model.</li> <li>– <i>R</i>: For the dynamic model. The state each document belongs to.</li> <li>– <i>P</i>: For the dynamic model. The state transition probability.</li> </ul> </li> <li>• <b>parallel_init</b>: Parallelize processes to speed up initialization. Default is FALSE. Please <code>plan()</code> before use this feature.</li> <li>• <b>resume</b>: The resume argument is used to save and load the intermediate results of the <b>keyATM</b> fitting process, allowing you to resume the fitting from a previous state. The default value is NULL (do not resume).</li> </ul>
keep	a vector of the names of elements you want to keep in output.

### Value

A `keyATM_output` object containing:

**keyword\_k** number of keyword topics

**no\_keyword\_topics** number of no-keyword topics

**V** number of terms (number of unique words)

**N** number of documents

**model** the name of the model

**theta** topic proportions for each document (document-topic distribution)

**phi** topic specific word generation probabilities (topic-word distribution)

**topic\_counts** number of tokens assigned to each topic

**word\_counts** number of times each word type appears

**doc\_lens** length of each document in tokens

**vocab** words in the vocabulary (a vector of unique words)

**priors** priors

**options** options

**keywords\_raw** specified keywords

**model\_fit** perplexity and log-likelihood

**pi** estimated  $\pi$  (the probability of using keyword topic word distribution) for the last iteration

**values\_iter** values stored during iterations

**kept\_values** outputs you specified to store in keep option

**information** information about the fitting

### See Also

[https://keyatm.github.io/keyATM/articles/pkgdown\\_files/Options.html](https://keyatm.github.io/keyATM/articles/pkgdown_files/Options.html)

### Examples

```
## Not run:
library(keyATM)
library(quanteda)
data(keyATM_data_bills)
bills_keywords <- keyATM_data_bills$keywords
bills_dfm <- keyATM_data_bills$doc_dfm # quanteda dfm object
keyATM_docs <- keyATM_read(bills_dfm)

# keyATM Base
out <- keyATM(docs = keyATM_docs, model = "base",
             no_keyword_topics = 5, keywords = bills_keywords)

# Visit our website for full examples: https://keyatm.github.io/keyATM/

## End(Not run)
```

keyATMvb

*keyATM with Collapsed Variational Bayes***Description****Experimental feature:** Fit keyATM base with Collapsed Variational Bayes**Usage**

```
keyATMvb(
  docs,
  model,
  no_keyword_topics,
  keywords = list(),
  model_settings = list(),
  vb_options = list(),
  priors = list(),
  options = list(),
  keep = list()
)
```

**Arguments**

docs	texts read via <a href="#">keyATM_read()</a>
model	keyATM model: base, covariates, and dynamic
no_keyword_topics	the number of regular topics
keywords	a list of keywords
model_settings	a list of model specific settings (details are in the online documentation)
vb_options	a list of settings for Variational Bayes <ul style="list-style-type: none"> <li>• <b>convtol</b>: the default is 1e-4</li> <li>• <b>init</b>: mcmc (default) or random</li> </ul>
priors	a list of priors of parameters
options	a list of options same as <a href="#">keyATM()</a> . Options are used when initialization method is mcmc.
keep	a vector of the names of elements you want to keep in output

**Value**

A keyATM\_output object

**See Also**[https://keyatm.github.io/keyATM/articles/pkgdown\\_files/keyATMvb.html](https://keyatm.github.io/keyATM/articles/pkgdown_files/keyATMvb.html)



---

keyATM\_data\_bills      *Bills data*

---

**Description**

Bills data

**Usage**

keyATM\_data\_bills

**Format**

A list with following objects:

**doc\_dfm** A quanteda dfm object of 140 documents. The text data is a part of the Congressional Bills scraped from CONGRESS.GOV.

**cov** An integer vector which takes one if the Republican proposed the bill.

**keywords** A list of length 4 which contains keywords for four selected topics.

**time\_index** An integer vector indicating the session number of each bill.

**labels** An integer vector indicating 40 labels.

**labels\_all** An integer vector indicating all labels.

**Source**

CONGRESS.GOV

---

keyATM\_read      *Read texts*

---

**Description**

Read texts and create a keyATM\_docs object, which is a list of texts.

**Usage**

```
keyATM_read(  
  texts,  
  encoding = "UTF-8",  
  check = TRUE,  
  keep_docnames = FALSE,  
  split = 0  
)
```

**Arguments**

<code>texts</code>	input. <code>keyATM</code> takes a quanteda dfm ( <code>dgCMatrix</code> ), <code>data.frame</code> , <b>tibble</b> <code>tbl_df</code> , or a vector of file paths.
<code>encoding</code>	character. Only used when <code>texts</code> is a vector of file paths. Default is UTF-8.
<code>check</code>	logical. If TRUE, check whether there is anything wrong with the structure of texts. Default is TRUE.
<code>keep_docnames</code>	logical. If TRUE, it keeps the document names in a quanteda dfm. Default is FALSE.
<code>split</code>	numeric. This option works only with a quanteda dfm. It creates a two subset of the dfm by randomly splitting each document (i.e., the total number of documents is the same between two subsets). This option specifies the split proportion. Default is 0.

**Value**

a `keyATM_docs` object. The first element is a list whose elements are split texts. The length of the list equals to the number of documents.

**Examples**

```
## Not run:
# Use quanteda dfm
keyATM_docs <- keyATM_read(texts = quanteda_dfm)

# Use data.frame or tibble (texts should be stored in a column named `text`)
keyATM_docs <- keyATM_read(texts = data_frame_object)
keyATM_docs <- keyATM_read(texts = tibble_object)

# Use a vector that stores full paths to the text files
files <- list.files(doc_folder, pattern = "*.txt", full.names = TRUE)
keyATM_docs <- keyATM_read(texts = files)

## End(Not run)
```

---

multiPGreg

*Run multinomial regression with Polya-Gamma augmentation*


---

**Description**

Run multinomial regression with Polya-Gamma augmentation. There is no need to call this function directly. The `keyATM` Covariate internally uses this.

**Usage**

```
multiPGreg(Y, X, num_topics, PG_params, iter = 1, store_lambda = 0)
```

**Arguments**

Y	Outcomes.
X	Covariates.
num_topics	Number of topics.
PG_params	Parameters used in this function.
iter	The default is 1.
store_lambda	The default is 0.

---

plot.strata\_doctopic *Plot document-topic distribution by strata (for covariate models)*

---

**Description**

Plot document-topic distribution by strata (for covariate models)

**Usage**

```
## S3 method for class 'strata_doctopic'
plot(
  x,
  show_topic = NULL,
  var_name = NULL,
  by = c("topic", "covariate"),
  ci = 0.9,
  method = c("hdi", "eti"),
  point = c("mean", "median"),
  width = 0.1,
  show_point = TRUE,
  ...
)
```

**Arguments**

x	a strata_doctopic object (see <a href="#">by_strata_DocTopic()</a> ).
show_topic	a vector or an integer. Indicate topics to visualize.
var_name	the name of the variable in the plot.
by	topic or covariate. Default is by topic.
ci	value of the credible interval (between 0 and 1) to be estimated. Default is 0.9 (90%).
method	method for computing the credible interval. The Highest Density Interval (hdi, default) or Equal-tailed Interval (eti).
point	method for computing the point estimate. mean (default) or median.
width	numeric. Width of the error bars.
show_point	logical. Show point estimates. The default is TRUE.
...	additional arguments not used.

**Value**

keyATM\_fig object.

**See Also**

[save\\_fig\(\)](#), [by\\_strata\\_DocTopic\(\)](#)

---

plot_alpha	<i>Show a diagnosis plot of alpha</i>
------------	---------------------------------------

---

**Description**

Show a diagnosis plot of alpha

**Usage**

```
plot_alpha(x, start = 0, show_topic = NULL, scales = "fixed")
```

**Arguments**

x	the output from a keyATM model (see <a href="#">keyATM()</a> ).
start	integer. The start of slice iteration. Default is 0.
show_topic	a vector to specify topic indexes to show. Default is NULL.
scales	character. Control the scale of y-axis (the parameter in <a href="#">ggplot2::facet_wrap()</a> ): free adjusts y-axis for parameters. Default is fixed.

**Value**

keyATM\_fig object

**See Also**

[save\\_fig\(\)](#)

---

plot_modelfit	<i>Show a diagnosis plot of log-likelihood and perplexity</i>
---------------	---------------------------------------------------------------

---

**Description**

Show a diagnosis plot of log-likelihood and perplexity

**Usage**

```
plot_modelfit(x, start = 1)
```

**Arguments**

`x` the output from a keyATM model (see [keyATM\(\)](#)).  
`start` integer. The starting value of iteration to use in plot. Default is 1.

**Value**

keyATM\_fig object.

**See Also**

[save\\_fig\(\)](#)

---

plot_pi	<i>Show a diagnosis plot of pi</i>
---------	------------------------------------

---

**Description**

Show a diagnosis plot of pi

**Usage**

```
plot_pi(  
  x,  
  show_topic = NULL,  
  start = 0,  
  ci = 0.9,  
  method = c("hdi", "eti"),  
  point = c("mean", "median")  
)
```

**Arguments**

x	the output from a keyATM model (see <a href="#">keyATM()</a> ).
show_topic	an integer or a vector. Indicate topics to visualize. Default is NULL.
start	integer. The starting value of iteration to use in the plot. Default is 0.
ci	value of the credible interval (between 0 and 1) to be estimated. Default is 0.9 (90%). This is an option when calculating credible intervals (you need to set store_pi = TRUE in <a href="#">keyATM()</a> ).
method	method for computing the credible interval. The Highest Density Interval (hdi, default) or Equal-tailed Interval (eti). This is an option when calculating credible intervals (you need to set store_pi = TRUE in <a href="#">keyATM()</a> ).
point	method for computing the point estimate. mean (default) or median. This is an option when calculating credible intervals (you need to set store_pi = TRUE in <a href="#">keyATM()</a> ).

**Value**

keyATM\_fig object.

**See Also**

[save\\_fig\(\)](#)

---

plot\_timetrend

*Plot time trend*

---

**Description**

Plot time trend

**Usage**

```
plot_timetrend(
  x,
  show_topic = NULL,
  time_index_label = NULL,
  ci = 0.9,
  method = c("hdi", "eti"),
  point = c("mean", "median"),
  xlab = "Time",
  scales = "fixed",
  show_point = TRUE,
  ...
)
```

**Arguments**

<code>x</code>	the output from the dynamic keyATM model (see <a href="#">keyATM()</a> ).
<code>show_topic</code>	an integer or a vector. Indicate topics to visualize. Default is NULL.
<code>time_index_label</code>	a vector. The label for time index. The length should be equal to the number of documents (time index provided to <a href="#">keyATM()</a> ).
<code>ci</code>	value of the credible interval (between 0 and 1) to be estimated. Default is 0.9 (90%). This is an option when calculating credible intervals (you need to set <code>store_theta = TRUE</code> in <a href="#">keyATM()</a> ).
<code>method</code>	method for computing the credible interval. The Highest Density Interval ( <code>hdi</code> , default) or Equal-tailed Interval ( <code>eti</code> ). This is an option when calculating credible intervals (you need to set <code>store_theta = TRUE</code> in <a href="#">keyATM()</a> ).
<code>point</code>	method for computing the point estimate. <code>mean</code> (default) or <code>median</code> . This is an option when calculating credible intervals (you need to set <code>store_theta = TRUE</code> in <a href="#">keyATM()</a> ).
<code>xlab</code>	a character.
<code>scales</code>	character. Control the scale of y-axis (the parameter in <a href="#">ggplot2::facet_wrap()</a> ): <code>free</code> adjusts y-axis for parameters. Default is <code>fixed</code> .
<code>show_point</code>	logical. The default is TRUE. This is an option when calculating credible intervals.
<code>...</code>	additional arguments not used.

**Value**

keyATM\_fig object.

**See Also**

[save\\_fig\(\)](#)

---

plot_topicprop	<i>Show the expected proportion of the corpus belonging to each topic</i>
----------------	---------------------------------------------------------------------------

---

**Description**

Show the expected proportion of the corpus belonging to each topic

**Usage**

```
plot_topicprop(
  x,
  n = 3,
  show_topic = NULL,
  show_topwords = TRUE,
```

```

    label_topic = NULL,
    order = c("proportion", "topicid"),
    xmax = NULL
  )

```

### Arguments

x	the output from a keyATM model (see <a href="#">keyATM()</a> ).
n	The number of top words to show. Default is 3.
show_topic	an integer or a vector. Indicate topics to visualize. Default is NULL.
show_topwords	logical. Show topwords. The default is TRUE.
label_topic	a character vector. The name of the topics in the plot.
order	The order of topics.
xmax	a numeric. Indicate the max value on the x axis

### Value

keyATM\_fig object

### See Also

[save\\_fig\(\)](#)

---

predict.keyATM\_output *Predict topic proportions for the covariate keyATM*

---

### Description

Predict topic proportions for the covariate keyATM

### Usage

```

## S3 method for class 'keyATM_output'
predict(
  object,
  newdata,
  transform = FALSE,
  burn_in = NULL,
  parallel = TRUE,
  posterior_mean = TRUE,
  ci = 0.9,
  method = c("hdi", "eti"),
  point = c("mean", "median"),
  label = NULL,
  raw_values = FALSE,
  ...
)

```



**Arguments**

object	the keyATM_output object for the covariate model.
newdata	New observations which should be predicted.
transform	Transform and standardize the newdata with the same formula and option as model_settings used in <a href="#">keyATM()</a> .
burn_in	integer. Burn-in period. If not specified, it is the half of samples. Default is NULL.
parallel	logical. If TRUE, parallelization for speeding up. Default is TRUE. Please <code>plan()</code> before use this function.
posterior_mean	logical. If TRUE, the quantity of interest to estimate is the posterior mean. Default is TRUE.
ci	value of the credible interval (between 0 and 1) to be estimated. Default is 0.9 (90%).
method	method for computing the credible interval. The Highest Density Interval ( <code>hdi</code> , default) or Equal-tailed Interval ( <code>eti</code> ).
point	method for computing the point estimate. <code>mean</code> (default) or <code>median</code> .
label	a character. Add a <code>label</code> column to the output. The default is NULL (do not add it).
raw_values	a logical. Returns raw values. The default is FALSE.
...	additional arguments not used.

---

read_keywords	<i>Convert a quanteda dictionary to keywords</i>
---------------	--------------------------------------------------

---

**Description**

This function converts or reads a dictionary object from quanteda to a named list. "Glob"-style wildcard expressions (e.g. `politic*`) are resolved based on the available terms in your texts.

**Usage**

```
read_keywords(file = NULL, docs = NULL, dictionary = NULL, split = TRUE, ...)
```

**Arguments**

file	file identifier for a foreign dictionary, e.g. path to a dictionary in YAML or LIWC format
docs	texts read via <a href="#">keyATM_read()</a>
dictionary	a quanteda dictionary object, ignore if file is not NULL
split	boolean, if multi-word terms be seperated, e.g. "air force" splits into "air" and "force".
...	additional parameters for <a href="#">quanteda::dictionary()</a>

**Value**

a named list which can be used as keywords for e.g. [keyATM\(\)](#)

**See Also**

[dictionary](#)

**Examples**

```
## Not run:
library(keyATM)
library(quanteda)
## using the moral foundation dictionary example from quanteda
dictfile <- tempfile()
download.file("http://bit.ly/37cV95h", dictfile)
data(keyATM_data_bills)
bills_dfm <- keyATM_data_bills$doc_dfm
keyATM_docs <- keyATM_read(bills_dfm)
read_keywords(file = dictfile, docs = keyATM_docs, format = "LIWC")

## End(Not run)
```

---

save\_fig

*Save a figure*

---

**Description**

Save a figure

**Usage**

```
save_fig(x, filename, ...)
```

**Arguments**

x	the keyATM_fig object.
filename	file name to create on disk.
...	other arguments passed on to the <a href="#">ggplot2::ggsave()</a> function.

**See Also**

[visualize\\_keywords\(\)](#), [plot\\_alpha\(\)](#), [plot\\_modelfit\(\)](#), [plot\\_pi\(\)](#), [plot\\_timetrend\(\)](#), [plot\\_topicprop\(\)](#), [by\\_strata\\_DocTopic\(\)](#), [values\\_fig\(\)](#)

---

semantic\_coherence      *Semantic Coherence: Mimno et al. (2011)*

---

### Description

Mimno, David et al. 2011. “Optimizing Semantic Coherence in Topic Models.” In Proceedings of the 2011 Conference on Empirical Methods in Natural Language Processing, Edinburgh, Scotland, UK.: Association for Computational Linguistics, 262–72. <https://aclanthology.org/D11-1024>.

### Usage

```
semantic_coherence(x, docs, n = 10)
```

### Arguments

x                      the output from a keyATM model (see [keyATM\(\)](#)).  
docs                    texts read via [keyATM\\_read\(\)](#).  
n                        integer. The number terms to visualize. Default is 10.

### Details

Equation 1 of Mimno et al. 2011 adopted to keyATM.

### Value

A vector of topic coherence metric calculated by each topic.

---

top\_docs                      *Show the top documents for each topic*

---

### Description

Show the top documents for each topic

### Usage

```
top_docs(x, n = 10)
```

### Arguments

x                      the output from a keyATM model (see [keyATM\(\)](#)).  
n                        How many documents to show. Default is 10.

### Value

An n x k table of the top n documents for each topic, each number is a document index.

---

top_topics	<i>Show the top topics for each document</i>
------------	----------------------------------------------

---

**Description**

Show the top topics for each document

**Usage**

```
top_topics(x, n = 2)
```

**Arguments**

x	the output from a keyATM model (see <a href="#">keyATM()</a> ).
n	integer. The number of topics to show. Default is 2.

**Value**

An n x k table of the top n topics in each document.

---

top_words	<i>Show the top words for each topic</i>
-----------	------------------------------------------

---

**Description**

If show\_keyword is TRUE then words in their keyword topics are suffixed with a check mark. Words from another keyword topic are labeled with the name of that category.

**Usage**

```
top_words(x, n = 10, measure = c("probability", "lift"), show_keyword = TRUE)
```

**Arguments**

x	the output (see <a href="#">keyATM()</a> and <a href="#">by_strata_TopicWord()</a> ).
n	integer. The number terms to visualize. Default is 10.
measure	character. The way to sort the terms: probability (default) or lift.
show_keyword	logical. If TRUE, mark keywords. Default is TRUE.

**Value**

An n x k table of the top n words in each topic

---

values_fig	<i>Get values used to create a figure</i>
------------	-------------------------------------------

---

**Description**

Get values used to create a figure

**Usage**

```
values_fig(x)
```

**Arguments**

x                    the keyATM\_fig object.

**See Also**

[save\\_fig\(\)](#), [visualize\\_keywords\(\)](#), [plot\\_alpha\(\)](#), [plot\\_modelfit\(\)](#), [plot\\_pi\(\)](#), [plot\\_timetrend\(\)](#), [plot\\_topicprop\(\)](#), [by\\_strata\\_DocTopic\(\)](#)

---

visualize_keywords	<i>Visualize keywords</i>
--------------------	---------------------------

---

**Description**

Visualize the proportion of keywords in the documents.

**Usage**

```
visualize_keywords(docs, keywords, prune = TRUE, label_size = 3.2)
```

**Arguments**

docs                a keyATM\_docs object, generated by keyATM\_read() function  
keywords            a list of keywords  
prune               logical. If TRUE, prune keywords that do not appear in docs. Default is TRUE.  
label\_size          the size of keyword labels in the output plot. Default is 3.2.

**Value**

keyATM\_fig object

**See Also**

[save\\_fig\(\)](#)

## Examples

```
## Not run:
# Prepare a keyATM_docs object
keyATM_docs <- keyATM_read(input)

# Keywords are in a list
keywords <- list(Education = c("education", "child", "student"),
                 Health    = c("public", "health", "program"))

# Visualize keywords
keyATM_viz <- visualize_keywords(keyATM_docs, keywords)

# View a figure
keyATM_viz

# Save a figure
save_fig(keyATM_viz, filename)

## End(Not run)
```

---

weightedLDA

*Weighted LDA main function*

---

## Description

Fit weighted LDA models.

## Usage

```
weightedLDA(
  docs,
  model,
  number_of_topics,
  model_settings = list(),
  priors = list(),
  options = list(),
  keep = c()
)
```

## Arguments

`docs` texts read via [keyATM\\_read\(\)](#).

`model` Weighted LDA model: base, covariates, and dynamic.

`number_of_topics` the number of regular topics.

`model_settings` a list of model specific settings (details are in the online documentation).

`priors` a list of priors of parameters.

**options** a list of options (details are in the documentation of `keyATM()`).

**keep** a vector of the names of elements you want to keep in output.

### Value

A `keyATM_output` object containing:

**V** number of terms (number of unique words)

**N** number of documents

**model** the name of the model

**theta** topic proportions for each document (document-topic distribution)

**phi** topic specific word generation probabilities (topic-word distribution)

**topic\_counts** number of tokens assigned to each topic

**word\_counts** number of times each word type appears

**doc\_lens** length of each document in tokens

**vocab** words in the vocabulary (a vector of unique words)

**priors** priors

**options** options

**keywords\_raw** NULL for LDA models

**model\_fit** perplexity and log-likelihood

**pi** estimated pi for the last iteration (NULL for LDA models)

**values\_iter** values stored during iterations

**number\_of\_topics** number of topics

**kept\_values** outputs you specified to store in `keep` option

**information** information about the fitting

### See Also

[https://keyatm.github.io/keyATM/articles/pkgdown\\_files/Options.html](https://keyatm.github.io/keyATM/articles/pkgdown_files/Options.html)

### Examples

```
## Not run:
library(keyATM)
library(quanteda)
data(keyATM_data_bills)
bills_dfm <- keyATM_data_bills$doc_dfm # quanteda dfm object
keyATM_docs <- keyATM_read(bills_dfm)

# Weighted LDA
out <- weightedLDA(docs = keyATM_docs, model = "base",
                  number_of_topics = 5)

# Visit our website for full examples: https://keyatm.github.io/keyATM/

## End(Not run)
```

# Index

## \* datasets

- keyATM\_data\_bills, 9
- by\_strata\_DocTopic, 3
- by\_strata\_DocTopic(), 11, 12, 18, 21
- by\_strata\_TopicWord, 4
- by\_strata\_TopicWord(), 20
- covariates\_get, 4
- covariates\_info, 5
- dictionary, 18
- ggplot2::facet\_wrap(), 12, 15
- ggplot2::ggsave(), 18
- keyATM, 5
- keyATM(), 3–5, 8, 12–20, 23
- keyATM-package, 2
- keyATM\_data\_bills, 9
- keyATM\_read, 9
- keyATM\_read(), 4, 5, 8, 17, 19, 22
- keyATMvb, 8
- multiPGreg, 10
- plot.strata\_doctopic, 11
- plot\_alpha, 12
- plot\_alpha(), 18, 21
- plot\_modelfit, 13
- plot\_modelfit(), 18, 21
- plot\_pi, 13
- plot\_pi(), 18, 21
- plot\_timetrend, 14
- plot\_timetrend(), 18, 21
- plot\_topicprop, 15
- plot\_topicprop(), 18, 21
- predict.keyATM\_output, 16
- predict.keyATM\_output(), 3
- quanteda::dictionary(), 17
- read\_keywords, 17
- save\_fig, 18
- save\_fig(), 12–16, 21
- semantic\_coherence, 19
- top\_docs, 19
- top\_topics, 20
- top\_words, 20
- values\_fig, 21
- values\_fig(), 18
- visualize\_keywords, 21
- visualize\_keywords(), 18, 21
- weightedLDA, 22