

Package ‘convert’

October 17, 2017

Version 1.52.0

Title Convert Microarray Data Objects

Author Gordon Smyth <smyth@wehi.edu.au>,
James Wettenhall <wettenhall@wehi.edu.au>,
Yee Hwa (Jean) Yang <jean@biostat.ucsf.edu>,
Martin Morgan <mtmorgan@fhcrc.org>Martin Morgan

Maintainer Yee Hwa (Jean) Yang <jean@biostat.ucsf.edu>

Depends R (>= 2.6.0), Biobase (>= 1.15.33), limma (>= 1.7.0), marray,
utils, methods

Description Define coerce methods for microarray data objects.

License LGPL

URL <http://bioinf.wehi.edu.au/limma/convert.html>

biocViews Infrastructure, Microarray, TwoChannel

NeedsCompilation no

R topics documented:

coerce	1
Index	4

coerce	<i>Convert Data Objects</i>
--------	-----------------------------

Description

Convert between limma, marray and Biobase data objects.

Details

Objects can be converted (coerced) from one class to another using `as(object, Class)` where `object` is an object to convert and `Class` is the name of the class to convert to. The following conversions are provided:

From:	To:
RGList	marrayRaw

```

marrayRaw  RGList
MAList     marrayNorm
marrayNorm MAList
RGList     NChannelSet
marrayRaw  NChannelSet
MAList     ExpressionSet
marrayNorm ExpressionSet

```

RGList and marrayRaw are coerced to NChannelSet. Channel values are not transformed.

MAList and marrayNorm are coerced so that the ExpressionSet slot contains log-ratios (M-values) and the ExpressionSet object has the same number of columns as the original object. In this case, information on the A-values is lost.

There is intentionally no conversion from RGList or marrayRaw to ExpressionSet, as ExpressionSet is intended for expression values, not intensities.

Author(s)

Gordon Smyth and others

See Also

[as](#) in the methods package.

Examples

```

##first set up some fake intensity matrices
testRed <- matrix(rnorm(5*2),5,2,
  dimnames=list(paste("gene",1:5, sep=""), c("S1", "S2")))
testGreen <- matrix(rnorm(5*2),5,2,
  dimnames=list(paste("gene",1:5, sep=""), c("S1", "S2")))

##some sample/target info
testTarget <- data.frame(slide=c("S1", "S2"), Cy3=c("T", "C"),
  Cy5=c("C", "T"), row.names=c("S1", "S2"))

maT <- new("marrayInfo", maLabels=c("S1", "S2"),
  maInfo= testTarget)

##now create instances and convert
x <- new("RGList")
x$R <- testRed
x$G <- testGreen
y <- as(x,"marrayRaw")
z <- as(x, "NChannelSet")

x <- new("marrayRaw")
x@maGf <- testGreen
x@maRf <- testRed
x@maTargets = maT
y <- as(x,"RGList")
z <- as(x, "NChannelSet")

x <- new("MAList")
y <- as(x,"marrayNorm")

```

```
##we construct a reasonably complete fake, small
##instance of the marrayNorm class
x <- new("marrayNorm")
x@maM <- testRed
x@maA <- testGreen
maTargets(x) = maT
y <- as(x,"MList")
y <- as(x, "ExpressionSet")

x <- new("MList")
x$M <- testRed
x$A <- testGreen
x$targets <- testTarget
y <- as(x,"ExpressionSet")
```

Index

*Topic **classes**

coerce, [1](#)

*Topic **data**

coerce, [1](#)

as, [2](#)

coerce, [1](#)

coerce, MAList, ExpressionSet-method
(coerce), [1](#)

coerce, MAList, marrayNorm-method
(coerce), [1](#)

coerce, marrayNorm, ExpressionSet-method
(coerce), [1](#)

coerce, marrayNorm, MAList-method
(coerce), [1](#)

coerce, marrayRaw, NChannelSet-method
(coerce), [1](#)

coerce, marrayRaw, RGList-method
(coerce), [1](#)

coerce, RGList, marrayRaw-method
(coerce), [1](#)

coerce, RGList, NChannelSet-method
(coerce), [1](#)

convert (coerce), [1](#)