

Package ‘logitT’

April 16, 2019

Version 1.40.0

Date 2008-09-14

Title logit-t Package

Author Tobias Guennel <tguennel@vcu.edu>

Maintainer Tobias Guennel <tguennel@vcu.edu>

Depends affy

Suggests SpikeInSubset

Description The logitT library implements the Logit-t algorithm introduced in
--A high performance test of differential gene expression for oligonucleotide arrays--
by William J Lemon, Sandya Liyanarachchi and Ming You for use with Affymetrix data
stored in an AffyBatch object in R.

License GPL (>= 2)

URL <http://www.bioconductor.org>

biocViews Microarray, DifferentialExpression

git_url <https://git.bioconductor.org/packages/logitT>

git_branch RELEASE_3_8

git_last_commit 1a00eeb

git_last_commit_date 2018-10-30

Date/Publication 2019-04-15

R topics documented:

logitTAffy 2

Index 3

logitTAffy

*Testing for differential gene expression using the Logit-t algorithm***Description**

This function takes an instance of `AffyBatch` and calculates t-statistics for tests of differential gene expression for oligonucleotide arrays using the Logit-t algorithm.

Usage

```
logitTAffy(object, group)
```

Arguments

<code>object</code>	an instance of <code>AffyBatch</code>
<code>group</code>	a vector specifying the group label for each array

Details

For more details see the package vignette.

Value

A named vector containing the t-statistics for each probe set for each array.

Author(s)

Tobias Guennel <tguennel@vcu.edu>

References

William J Lemon, Sandya Liyanarachchi and Ming You (2003). A high performance test of differential gene expression for oligonucleotide arrays. *Genome Biology* 2003, 4:R67. <http://genomebiology.com/2003/4/10/R67>

See Also

[AffyBatch](#)

Examples

```
if(require(SpikeInSubset)){
  library(SpikeInSubset)
  data(spikein95)
  logitTex<-logitTAffy(spikein95, group=c("A","A","A","B","B","B"))
  logitTex[1:10] # extract t-statistics for first ten probe sets
  logitTex[grep("AFFX-BioB-5_at",names(logitTex))] # extract t-statistics for specific probe sets
  pvals<-(1-pt(abs(logitTex),df=4))*2 # calculate two-sided p-values
  signifgenes<-names(logitTex)[pvals<0.01] # find significant probe sets at 0.01 significance level
}else{
  stop("Please install the SpikeInSubset package to run the example.")
}
```

Index

AffyBatch, 2

logitTAffy, 2